



SVN-2500P Series H.265 NVR



Features

- Dual Stream Recording
- 5MP / 4MP / 3MP / 1080P / 960P / 720P
- H.265 High Profile Compression
- Intuitive and User-Friendly GUI
- Windows Style Easy Operation

More Features

- 4K Output, True High Resolution Display
- Pentaplex: Preview, Record, Playback, Backup and Remote Access
- Remote Control via IE or CMS: Preview, Playback, Backup, PTZ and Configuration
- iOS and Android Support Mobile Device
- Search: Time Slice / Time / Event / Tag Search
- Authorization Management, Log View and Device Status View
- Support PTZ Preset and Auto Cruise, Up To 255 Presets and 8 Cruises
- Support NAT Function and QRCode Scanning by Mobile Phone and PAD Alarm Triggering: Record, Snap, Present, E-mail, Etc
- 10 Multi Users Online Simultaneously
- HDD Storage 4/8 CH 1 HDD Max 8TB, 32 CH 8 x SATA HDD, Max 8TB each, 1 x e-SATA

	Specification	SVN-2504P4	SVN-2508P8	SVN-2532P16
SYSTEM	COMPRESSION	STANDARD H.265 HEVC (HIGH EFFICIENCY VIDEO CODING) & H.264		
	OS	EMBEDDED LINUX		
VIDEO	NETWORK INPUT	4 CH IPC INPUT	8 CH IPC INPUT	32 CH IPC INPUT
	NETWORK ACCESS BANDWIDTH	40Mbps	64Mbps	256Mbps
	NETWORK ACCESS FORMAT	5MP / 4MP / 3MP / 1080P / 960P / 720P @ 25FPS / 30FPS		
	OUTPUT	HDMI x 1: 4K (3840 x 2160) / 1080P (1920 x 1080) / 720P (1280 x 1024), VGA x 1: 1920 x 1080 / 1280 x 1024		
AUDIO	NETWORK INPUT	4 CH IPC AUDIO INPUT	8 CH IPC AUDIO INPUT	32 CH IPC AUDIO INPUT
	2-WAY AUDIO	RCA *1		
	LOCAL OUTPUT	RCA *1		
RECORD	RESOLUTION	5MP / 4MP / 3MP / 1080P / 960P / 720P		
	MODE	MANUAL, TIMER, MOTION, SENSOR		
PLAYBACK	SIMULTANEOUS PLAYBACK	MAX. 4 CH	MAX. 8 CH	MAX. 16 CH
	SMART SEARCH	HIGHLIGHTED COLOR TO DISPLAY THE CAMERA RECORD IN A CERTAIN PERIOD OF TIME, DIFFERENT COLORS REFERS TO DIFFERENT RECORD EVENTS		
	FUNCTION	PLAY, PAUSE, FF, FB, DIGITAL ZOOM, ETC.		
ALARM	MODE	MANUAL, SENSOR, MOTION, EXCEPTION		
	INPUT / OUTPUT	SUPPORT IPC ALARM INPUT / OUTPUT		16 CH LOCAL AND IPC ALARM INPUT / 4 CH OUTPUT
NETWORK	INTERFACE	RJ45 10 / 100 Mbps x 1		
	PoE PORT	RJ45 x 4	RJ45 x 8	RJ45 x 16
	PROTOCOL	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPNP, NTP, SMTP		
BACKUP	LOCAL BACKUP	USB FLASH DRIVE, U DISC (Express and Flexible)		
	NETWORK BACKUP	YES, Express and Flexible		
PORT	USB	USB 2.0 x 2 (FRONT PANEL)		USB 2.0 x 1 (FRONT PANEL), USB 3.0 x 1 (REAR PANEL)
	REMOTE CONTROLLER	OPTIONAL		YES
PHYSICAL	POWER SUPPLY	DC 48V		ATX
	CONSUMPTION	≤ 5W (NO HDD)	≤ 10W (NO HDD)	≤ 15W (NO HDD)
	DIMENSION (WxHxD)	255mm x 210mm x 42mm		430 mm x 450 mm x 89 mm
	Operation Temp	-14 °F ~ 122 °F, 10% ~ 90% HUMIDITY		