

Outdoor Vandal Dome Camera NVD-183



Features

- High Resolution – 650 TV Lines
- IP68 Waterproof / Vandal Proof
- Easy Twist & Lock Installation
- 3 Axis Bracket – Wall or Ceiling Mount
- 2.8~12mm Auto Iris Varifocal Lens
- 3DDNR Digital Noise Reduction
- Dual Power: 12VDC/24VAC
- OSD for Easy Camera Set-up

More Features

- 1/3" Sony Super HAD II CCD
- SENS-UP – Enhanced Low Light Imaging
- Single Scan Wide Dynamic Range
- 10X Digital Zoom Function
- Full Day/Night Function
- Privacy Masking - 6 Zones
- Motion Detection – 240 Zones
- DIS - Digital Image Stabilizer
- LSC - Lens Shading Compensation
- HLM - High Light Mask Function

Specifications	NVD-183
Image Sensor	1/3" SONY Super HAD II CCD
Resolution	650 TV Lines
Lens	2.8 ~ 12mm Auto-Iris Varifocal Lens
Scanning System	2:1 Interlaced
S/N Ratio	More than 50 dB (AGC Off)
Video Output	1.0 Vp-p Composite Video, 75 Ohms
Electronic Shutter Speed	Auto/Manual (1/60sec ~ 1/100,000sec)
Minimum Illumination	0.3 Lux at F1.2 (Color) / 0.002 Lux(B/W Sens-up x256)
Backlight Compensation	Low / Middle / High / HLM / Off Selectable
Auto Gain Control (AGC)	Low / Middle / High / Off Selectable
White Balance	ATW / AWC / PUSH / Manual
Digital Noise Reduction	3DDNR - Low / Middle / High / Off Selectable
Day/Night Function	Auto / Color / BW / CDS
Wide Dynamic Range	WDR - Auto / Off
Digital Zoom	On (1~10X) / Off
Privacy Masking	On / Off (6 Zones)
Motion Detection	On / Off (240 Zones)
Sharpness	Adjustable
OSD	Built-In On Screen Display
Housing	IP68 Waterproof & Vandal-Resistant Case
Power	12V DC / 24V AC Auto Detection
Operating Temperature	14°~104° F (-10°~40° C)
Dimensions / Weight	W x H: 5.5 x 4.0 inches / 14 x 10.1 cm, 2.5lbs / 1.13kg