

Features



H.264 High Profile Compression
Hybrid HD-TVI / Analog
Composite BNC

More Features

Mobile App

“Super Live Pro”

- Multi Screen Viewing
- Record
- Snapshot
- PTZ Control
- Save Device List

| Specification | EPD-6000 |
|-----------------------------|---|
| OPERATING SYSTEM / FIRMWARE | EMBEDDED LINUX / LINUX OS IN FLASH MEMORY |
| MEMORY | 2GB DDR3 MEMORY |
| VIDEO INPUT | 8 BNC / 4 IP (CH 1-4) |
| VIDEO OUTPUT | COMPOSITE BNC x 2 / VGA / HDMI |
| RECORDING RATE (MAX) | 720; 240/200 FPS(NTSC/PAL), 1080; 240/200 FPS (NTSC/PAL) |
| AUDIO INPUT/OUTPUT | 16/1 |
| ALARM INPUT / ALARM OUTPUT | 16/1 RELAY / 8TTL/2 (RELAY) |
| MASTER ALARM | 1 |
| ALARM OUTPUT | 8TTL/2 (RELAY) |
| USB 2.0 | 4*USB (2* FRONT PANEL, 2 * REAR PANEL) |
| ETHERNET | R345 10M/100M/1000M ETHERNET |
| USER INTERFACE (GUI) | KEYPAD, MOUSE, PTZ CONTROL, REMOTE CONTROLLER |
| ARCHIVE FILE FORMAT | EXE (VIDEO CLIP) AVI (VIDEO CUP) /JPEG (STILL IMAGE) |
| NIP SERVER | YES |
| GMT TIME ZONE / AUTO DST | YES / YES |
| RECORDING QUALITIES | SUPER/HIGH/STANDARD/LOW |
| RECORDING MODES | CONTINUOUS/ALARM/MOTION/EMERGENCY |
| MOTION DETECTION | YES 30*20 |
| PLAYBACK CONTROL | x1, x2, x4, x8, *16, x32, x64, EXTREME |
| PTZ CONTROL | RS 485/422 (TERMINAL BLOCK), UTC OVER BNC (CONTROL OVER COAX) |
| TEXT INSERTION (POS) | 4 |
| CENTRAL MONITORING STATION | CMS PRO (WINDOWS)/CMS(MAC) / WEB CLIENT PRO |
| MOBILE VIEWER | AVY VIEWER HD (Ipad/Iphone/ANDROID) |
| PRIMARY STORAGE | 4 * SATA HDD (UP TO 24 TB), 1 *ODD(DVD-RW) |
| eSATA | 1 PORT |
| CLIP COPY STORAGE | BUILT IN INTERNAL DVD-RW, USB MEMORY STICK, OVER THE NETWORK |
| DIMENSION (WxHxD) | 430mm *88mm * 430mm(MOUNTABLE) |
| OPERANIG TEMPERATURE | 5 C-40 C/41 F-104F (HUMIDITY 0%-90%) |
| POWER ADAPTER | DC 12V,6.67 A |
| POWER CONSUMPTION | <72W (WITHOUT HDD) |