

**OPTICOM****SVD-2400****Silver Series Hybrid DVR (4/8/16 Channel)**

## Features



H.264 High Profile Compression

HDMI &amp; VGA Output

2 Way Audio

720p / 1080p

Hybrid HD-TVI / Analog / AHD

### More Features

Mobile App

**“Super Live Pro”**

- Multi Screen Viewing
- Record
- Snapshot
- PTZ Control
- Save Device List

Specification	SVD-2404	SVD-2408	SVD-2416
SYSTEM CPU	Cortex A9		
SYSTEM OS	Embedded Linux		
VIDEO INPUT	4 BNC + 1 IP (CHS)	8 BNC + 1 IP (CH.9-12)	16 BNC + 1 IP (CH.17-24)
INPUT/OUTPUT	RCA *1 / RCA *1		
RESOLUTION	1080P (1920 *1080),720P(1280*720),(960*480)		
FRAME RATE	720P 480FPS (NTSC) 400FPS (PAL)		
	1080P 60FPS (NTSC)	1080P 120FPS (NTSC)	1080P 240FPS (NTSC)
RECORD BITRATE	1-6 MBPS		
RECORD ENCODE	VBR/CBR		
RECORD QUALITY	6 Level		
RECORD MODE	Manual, TIMER, MOTION		
FILE MANAGER	LOCK, UNLOCK, RESERVING TIME		
RESOLUTION	3MP/1080P/960P/720P/WD1/D1		
FRAME RATE (FPS)	3MP:15FPS(NTSC), 1080P/960P/720P:30FPS(NTSC) PER CHANNEL		
PLAYBACK	4 CHANNEL / 8 CHANNEL / 8 CHANNEL		
SEARCH	TIME, MOTION, SINGEL OR MULTI CHANNEL		
FUNCTION	PLAY, PAUSE, FF,FB, DIGITAL ZOOM		
ALARM MODE	MOTION, VIDEO LOSS		
ALARM INPUT/OUTPUT	N / A		
ALARM TRIGGERING	RECORD, PTZ PRESET, E-MAIL		
INTERFACE	R145 10M/100M/1000M ETHERNET NETWORK PORT		
PROTOCOL	TCP, IP, UDP, DHCP, DNS, DONS		
USERS	8 USERS ONLINE, DUAL STREAM		
HDD	SATA * 1 (UP TO 6TB)		SATA * 2 (UP TO 12TB)
RS485	RS 485 *1		
USB	USB 2.0*2, MOUSE & BACKUP		
IR CONTROLLER	REMOTE CONTROLLER		
POWER SUPPLY	DC 12 V, 2A	DC 12V, 3A	DC 12V, 4A
CONSUMPTION	<9W(WITHOUT HDD)	<14W(WITHOUT HDD)	<20W(WITHOUT HDD)
DIMENSION	255mm * 210mm *42mm		430mm * 300mm *55mm
OPERATE TEMP	10C -50C, 10% -90% HUMIDITY		

Opticom Tech  
[www.opticomtech.com](http://www.opticomtech.com)  
[www.toughestvideocamera.com](http://www.toughestvideocamera.com)

Sales Office: 800-578-1853  
 Sales Fax: 888-370-5656  
 Sales E-mail: [Info@OpticomTech.com](mailto:Info@OpticomTech.com)