

Industrial LCD CCTV Monitors

LCDI-104, LCDI-104H



Features

- High Resolution 10.4" TFT Panel
- Dual BNC Inputs & Outputs
- VGA Input / PIP (Picture-In-Picture)
- 3D De-Interlace Technology
- Automatic Color Control
- 3D Comb Filter Technology
- User Friendly Controls & OSD

Specifications	LCDI-104	LCDI-104H
Operating System	NTSC / PAL Auto Switch	
LCD Panel	10.4" TFT LCD Panel	
Viewable Area	221.0 x 158.4 mm (HV)	210.4 x 157.8 mm (HV)
Aspect Ratio	4:3	
Resolution	800 x 600	1024 x 768
Display Colors	16.7M (8 Bit for RGB)	16.2M
Brightness (nit)	400 (LED BL)	300
Contrast Ratio	700:1	500:1
Viewing Angle (U/D/L/R)	60/80/80/80	50/60/70/70
Input Video Signal	2x Composite Video, 1.0 Vp-p, 75 Ohms; 1 x S-Video; 1 x Analog RGB	
Audio	2 x Audio Inputs, 50~100m Vp-p; 1 x Earphone Out	
Panel Frame	Aluminum	
Controls	Source / Menu / Item / Adjust (Up / Down) / Power	
Video Connector	2 x BNC In; 2 x BNC Out; 1 x 4P Mini DIN In; 1 x 15 Pin D-Sub	
Audio Connector	2 x RCA Jack In; 1 x Earphone Out; 2 x Audio Speaker (2W + 2W)	
Operating Temperature	32°~122° F (0°~50° C)	32°~122° F (0°~50° C)
Power Supply	90~264 VAC, 60/50 Hz, Global Switching Power Supply (12V 3A)	
Power Consumption	10W	15W
Dimensions (W x H x D)	10.5 x 8.4 x 2.3 Inch / 26.6 x 21.3 x 5.7 cm	
Weight	4.4 lbs / 2.0 kg	2.2 lbs / 4.9 kg