

**OPTICOM**

# High Definition LCD CCTV Monitors

## LCDI-15HDM, LCDI-17HD/HDM, LCDI-19HD/HDM



## Features

- Full High Definition LCD Monitors
- HDMI, DVI & Analog (BNC) Inputs
- 3D De-Interlace Technology
- Automatic Color Control
- User Friendly Controls & OSD
- 3D Comb Filter Technology

Specifications	LCDI-15HD	LCDI-17HD	LCDI-17HDM	LCDI-19HD	LCDI-19HDM
Operating System	NTSC / PAL Auto Switch				
LCD Panel	15" TFT	17" TFT		19" TFT	
Viewable Area	304 x 220 mm (H/V)	338 x 270 mm (H/V)		376 x 301 mm (H/V)	
Aspect Ratio	4:3				
Maximum Resolution	1024 x 768 (H/V)	1280 x 1024 (H/V)			
Display Colors	16.2M	16.7M			
Brightness	300 nit	400 nit			
Contrast Ratio	500:1	800:1		1000:1	
Response Time (Tr/Tf)	6 / 19 ms	3.5 / 1.5 ms		3.6 / 1.4 ms	
Viewing Angle (U/D/L/R)	60/50/75/75	80/80/80/80		80/80/85/85	
Input Video Signal	Composite Video, 1.0 Vp-p, 75 Ohms; Full HD (DVI/HDMI)				
Audio	1 Channel RCA In: 50~100m Vp-p / 2W Max; 1 x Earphone Out				
Impedance	75 Ohms Auto Termination (Input / Output)				
Panel Frame	High Impact Plastic	High Impact Plastic	Metal	High Impact Plastic	Metal
Bracket	VESA Standard 100 / 75				
Video Connector	2 x BNC In; 2 x BNC Out; 1 x 4P Mini DIN In; 1 x 15 Pin D-Sub, 1 x DVI, 1 x HDMI				
Operating Temperature	32°~104° F (0°~40° C)				
Power Supply	90~260 VAC, Global Switching Power Supply (12V 5A)				
Power Consumption	18W	30W		33W	
Dimensions (W x H x D)	14.1 x 11.1 x 2.5 inches 35.7 x 31.0 x 6.4 cm	15.4 x 12.8 x 2.7 inches 39.1 x 32.5 x 6.9 cm		16.9 x 14.0 x 2.5 inches 43.0 x 35.6 x 6.7 cm	
Weight	7.1 lbs / 3.2 kg	9.9 lbs / 4.5 kg		10.6 lbs / 4.8 kg	

**Opticom Technologies Inc.**  
[www.opticomtech.com](http://www.opticomtech.com)  
[www.toughestvideocamera.com](http://www.toughestvideocamera.com)

**USA Sales:**  
**Canada:**

Battle Creek, Michigan:  
 Head Office (Vancouver):  
 Quebec (Montreal):  
 Maritimes (St. John):

800-578-1853  
 855-569-3240  
 888-222-3321  
 888-224-3450