

OPTICOM**HD Wide Screen LCD CCTV Monitors**

LCDI-215HDML, LCDI-27HDM, LCDI-32HDM, LCDI-42HDML

**Features**

Full HD Wide Screen (16:9 Ratio)
 21.5", 27", 32" & 42" Models
 HDMI, DVI & Analog (BNC) Inputs
 3D De-Interlace Technology
 Advanced Video Processor
 User Friendly Controls & OSD
 3D Comb Filter / LED Backlight

Specifications	LCDI-215HDML	LCDI-27HDM	LCDI-32HDM	LCDI-42HDML
Operating System	NTSC / PAL Auto Switch			
LCD Panel	21.5" Wide Screen	27" Wide Screen	32" Wide Screen	42" Wide Screen
Viewable Area	477 x 268 mm (H/V)	698 x 336 mm (H/V)	698 x 393 mm (H/V)	930 x 523 mm (H/V)
Aspect Ratio	16:9			
Maximum Resolution	1920 x 1080 (H/V)			
Display Colors	16.7M			
Brightness (nit)	250 (LED BL)	450 (LED BL)	400 (LED BL)	450 (LED BL)
Contrast Ratio	5000:1		4000:1	
Response Time (Tr/Tf)	3.8 / 1.2	7 / 5	8 (G to G)	5.5 (G to G)
Viewing Angle (U/D/L/R)	89/89/89/89			
Input Video Signal	Composite Video, 1.0 Vp-p, 75 Ohms; Full HD (DVI/HDML)			
Audio	2 x RCA In (L/R): 50~100m Vp-p; 1 x PC Audio In			
Impedance	75 Ohms Auto Termination			
Panel Frame	Aluminum			
Bracket	VESA Standard 100 / 200			
Video Connector	1 x BNC In; 2 x BNC Out; 1 x 4P Mini DIN In; 1 x 15 Pin D-Sub, 1 x DVI, 1 x HDMI, 1 x USB			
Operating Temperature	32°~122° F (0°~50° C)			
Power Supply	90~264 VAC, Global Switching Power Supply			
Power Consumption	22W	28.5W	58W	85W
Dimensions (W x H x D)	20.9x 12.7 x 2.23 inches 53.2 x 32.3 x 5.7 cm	25.6 x 15.6 x 2.4 inches 65.8 x 39.6 x 6.1 cm	29.7 x 17.8 x 3.4 inches 75.6 x 45.3 x 8.7 cm	40.1 x 24.1 x 4.8 inches 101.8 x 61.1 x 12.2 cm
Weight	11.9 lbs / 5.4 kg	15.4 lbs / 7.1 kg	30.9 lbs / 14 kg	61.7 lbs / 28 kg

Opticom Technologies Inc.
www.opticomtech.com
www.toughestvideocamera.com

USA Sales:
Canada:

Battle Creek, Michigan:
 Head Office (Vancouver):
 Quebec (Montreal):
 Maritimes (St. John):

800-578-1853
 855-569-3240
 888-222-3321
 888-224-3450