

Compact LCD Monitors

LCDI-56L, LCDI-7L



Features

- High Resolution TFT LCD Panel
- 2 Channels Video / 1 Ch. Audio
- Compact 5.6" & 7.0" Models
- LED Backlight
- High Impact Case with Stand
- User Friendly Controls & OSD

Specifications	LCDI-56L	LCDI-7L
Operating System	NTSC / PAL Auto Switch	
LCD Panel	5.6" TFT LCD Panel	7.0" TFT LCD Panel
Aspect Ratio	4:3	16:9
Resolution	640 x 480	1440 x 234
Brightness (nit)	250 (LED BL)	400 (LED BL)
Contrast Ratio	500:1	400:1
Viewing Angle (U/D/L/R)	50/70/70/70	40/65/65/65
Input Video Signal	2 Channels Video, 1.0 Vp-p, 75 Ohms	
Audio	1 Channel / (MONO) 30m~100mVp-p	
Panel Frame	High Impact Plastic	
Controls	Front Panel Controls / OSD	
Video Connector	Mini Phone Jack	
Audio Connector	Mini Phone Plug to RCA Adaptor	
PC Connector	15 Pin D-Sub (Optional)	
Operating Temperature	32°~122° F (0°~50° C)	32°~122° F (0°~50° C)
Power Supply	12V DC	
Power Consumption	3.6W	4.1W
Dimensions (W x H x D)	6.3 x 5.2 x 1.5 Inch / 16.0 x 13.3 x 3.7 cm	7.1 x 4.7 x 0.8 Inch / 17.9 x 12.0 x 2.1 cm
Weight	0.84 lbs / 0.38 kg	0.8 lbs / 0.35 kg