



MIB-2100SV

2MP IR Bullet Camera



Features

- 3.6mm FIXED LENS
- H.264
- 36 IR LED / 90ft Distance
- ICR AUTO SWITCH
- 3DDNR / DWDR

More Features

- ROI CODING
- POE (POWER OVER ETHERNET) POWER SUPPLY
- SUPPORT SMART PHONE, IPAD, REMOTE MONITORING
- SUPPORT P2P / TRIPLE STREAMS
- WATER PROOF (IP66)
- DC 12V / WHITE CASING

Specification	MIB-2100SV
IMAGE SENSOR	1 / 3" CMOS
IMAGE SIZE	1920 x 1080
ELECTRONIC SHUTTER	1 / 25s ~ 1 / 100000s
MIN. ILLUMINATION	0 LUX (IR LED ON)
LENS	3.6mm FIXED LENS
LENS MOUNT	M12
VIDEO COMPRESSION	H.264 / MJPEG
RESOLUTION	1080P (1920 X 1080), 720P (1280 X 720), D1, CIF, 480 X 240
MULTI-STREAM	1920 X 1080 (1 ~ 30FPS) / 1280 X 720 (1 ~ 30FPS) / 1280 X 720 (1 ~ 10FPS) / D1 (1 ~ 30FPS) / CIF (1 ~ 30FPS) / CIF (1 ~ 30FPS) / 480 X 240 (1 ~ 30FPS)
BIT RATE	64 Kbps ~ 8 Mbps
ENCODE MODE	VBR / CBR
QUALITY	FIVE LEVELS UNDER VBR; FREELY ADJUSTABLE UNDER CBR
IMAGE SETTINGS	CORRIDOR PATTERN, SATURATION, BRIGHTNESS, CHROMA, CONTRAST, WIDE DYNAMIC, SHARPEN, NR, ETC. ADJUSTABLE THROUGH CLIENT SOFTWARE OR WEB BROWSER
REMOTE MONITORING	IE BROWSING, CMS REMOTE CONTROL
ONLINE CONNECTION	SUPPORT SIMULTANEOUS MONITORING FOR UP TO 4 USERS; SUPPORT MULTI-STREAM REAL TIME TRANSMISSION
PROTOCOL	TCP / IP, UDP, DHCP, NTP, RTSP, PPPOE, DDNS, PROTOCOL SMTP, FTP
STORAGE	NETWORK REMOTE STORAGE
SMART ALARM	MOTION ALARM
DAY & NIGHT	ICR
POE	YES
IR DISTANCE	20 ~ 30m
WATER-PROOF	IP66
NETWORK	RJ45
AUDIO	NO
POWER SUPPLY	DC 12V / POE
OPERATING ENVIRONMENT	-22°F ~ 122°F, 10% ~ 90% HUMIDITY
DIMENSIONS	ø87 x 219mm (ø3.4 x 8.6in)