



MIB-2107SV

2 MEGAPIXEL IP IR BULLET CAMERA

Features



2.8~12mm VARIFOCAL LENS

H.264

48 IR LED / 180ft Distance

ICR AUTO SWITCH

More Features

30 ~ 50m IR NIGHT VIEW DISTANCE

3D DNR, DIGITAL WDR SUPPORT CORRIDOR PATTERN

ROI CODING

POE (POWER OVER ETHERNET) POWER SUPPLY

SUPPORT SMART PHONE, IPAD, REMOTE MONITORING

SUPPORT P2P / TRIPLE STREAMS

WATER PROOF (IP66)

DC 12V / WHITE CASING

Specification	MIB-2107SV
IMAGE SENSOR	1 / 3" CMOS
ELECTRONIC SHUTTER	1 / 25s ~ 1 / 100000s
MIN. ILLUMINATION	0 LUX (IR LED ON)
LENS	2.8~12mm VARIFOCAL LENS
VIDEO COMPRESSION	H.264 / MJPEG
RESOLUTION	1080P (1920 X 1080), 720P (1280 X 720), D1, CIF, 480 X 240
MULTI-STREAM	1920 X 1080 (1 ~ 30FPS) / 1280 X 720 (1 ~ 30FPS) / 1280 X 720 (1 ~ 10FPS) / D1 (1 ~ 30FPS) / CIF (1 ~ 30FPS) / 480 X 240 (1 ~ 30FPS)
BIT RATE	64 Kbps ~ 8 Mbps
ENCODE MODE	VBR / CBR
QUALITY	FIVE LEVELS UNDER VBR; FREELY ADJUSTABLE UNDER CBR
IMAGE SETTINGS	CORRIDOR PATTERN, SATURATION, BRIGHTNESS, CHROMA, CONTRAST, WIDE DYNAMIC, SHARPEN, NR, ETC. ADJUSTABLE THROUGH CLIENT SOFTWARE OR WEB BROWSER
REMOTE MONITORING	IE BROWSING, CMS REMOTE CONTROL
ONLINE CONNECTION	SUPPORT SIMULTANEOUS MONITORING FOR UP TO 4 USERS; SUPPORT MULTI-STREAM REAL TIME TRANSMISSION
PROTOCOL	TCP / IP, UDP, DHCP, NTP, RTSP, PPPOE, DDNS, PROTOCOL SMTP, FTP
STORAGE	NETWORK REMOTE STORAGE
SMART ALARM	MOTION ALARM
DAY & NIGHT	ICR
POE	YES
IR DISTANCE	30 ~ 50m
WATER-PROOF	IP66
NETWORK	RJ45
AUDIO	NO
STORAGE CARD	SUPPORT TF CARD, THE MAX CAPACITY IS 64GB
POWER SUPPLY	DC 12V / POE
POWER CONSUMPTION	< 2.5W / < 6.5W w/ IR on
OPERATING TEMP	-22°F ~ 122°F, 10% ~ 90% HUMIDITY
DIMENSIONS	ø87 x 219mm (ø3.4 x 8.6in)
WEIGHT (NET)	1091g (2.4 lbs)