



# MIB-5131SV

## 5 MP H.265 IR BULLET CAMERA



### Features

- 3.6mm Fixed Lens
- 42 LEDs / 160ft Distance
- ICR Auto Switch
- DWDR
- 2D / 3D DNR

### More Features

3D DNR, DIGITAL WDR

SUPPORT 8 ROI CODING

ONE GIGABIT ETHERNET NETWORK PORT, 10M / 100M / 1000M SELF-ADAPTIVE

SUPPORT SD CARD LOCAL STORAGE, UP TO 64 GB

SUPPORT CVBS LOCAL VIDEO, TWO-WAY AUDIO AND POE POWER SUPPLY

SUPPORT SMART PHONE, IPAD, REMOTE MONITORING

SUPPORT P2P

Specification	MIB-5131SV
IMAGE SENSOR	1 / 1.8" CMOS
EFFECTIVE PIXELS	2592 x 1944
ELECTRONIC SHUTTER	1 / 25S ~ 1 / 100000S
MIN. ILLUMINATION	COLOR: 0.0Lux@F1.2, AGC ON, B/W: 0Lux WITH IR
LENS	3.6mm FIXED LENS
BLC	YES
VIDEO COMPRESSION	H.265 MP, H.264 BL/MP/HP, MJPEG
AUDIO COMPRESSION	G.711A / G.711U
BIT-RATE	64Kbps ~ 10Mbps
ENCODE MODE	VBR / CBR
IMAGE QUALITY	FIVE LEVELS UNDER VBR; FREELY ADJUSTABLE UNDER CBR
RESOLUTION	5MP (2592x1944), 2K (2560x1440), 1080P(1920x1080), 720P(1280x720), D1, CIF, 480x240
MULTI-STREAM	5MP(1~30fps) / 2K(1~30fps) / 1080P(1~30fps) / 720P(1~30fps) / 720P(1~5fps) / D1(1~10fps) / CIF(1~30fps) / D1(1~30fps) / CIF(1~30fps) / 480x240(1~30fps)
IMAGE SETTINGS	ROI, SATURATION, BRIGHTNESS, HUE, CONTRAST, WDR, SHARPNESS, DNR, ETC
NETWORK	RJ45
VIDEO OUTPUT	CVBS (BNC x 1)
AUDIO	ONE-WAY AUDIO(MIC IN x 1)
REMOTE MONITORING	BROWSER, CVMS, MOBILE CVMS
SUPPORTED BROWSERS	IE / CHROME / FIREFOX / SAFARI
ONLINE CONNECTION	10 ONLINE USERS
PROTOCOL	TCP/IP, UDP, DHCP, NTP, RTSP, PPPOE, DDNS, SMTP, FTP
CONNECTION PROTOCOL	ONVIF
STORAGE	NETWORK REMOTE STORAGE
SMART ALARM	MOTION ALARM
INTELLIGENT ANALYSIS	PEA / OSC / AVD
WATER-PROOF	IP66
POWER SUPPLY	DC 12V/PoE
IR CONSUMPTION	< 2.5W / < 6W w/ IR on
WORKING ENVIRONMENT	-22°F ~ 122°F, 10% ~ 90% HUMIDITY
DIMENSIONS	F87mm x 219mm
WEIGHT	617g