



MIB-5141SV

4 MP H.265 IR BULLET CAMERA



Features

- 3.6-10mm Varifocal
- 48 LEDs / 180ft Distance
- ICR Auto
- DWDR
- 2D / 3D DNR

More Features

SUPPORT 8 ROI CODING

ONE GIGABIT ETHERNET NETWORK PORT, 10M / 100M / 1000M SELF-ADAPTIVE

SUPPORT SD CARD LOCAL STORAGE, UP TO 128GB

SUPPORT CVBS LOCAL VIDEO, TWO-WAY AUDIO AND POE POWER SUPPLY

SUPPORT SMART PHONE, IPAD, REMOTE MONITORING

SUPPORT P2P

SUPPORT THREE STREAMS

BACKLIGHT COMPENSATION

ONVIF CONNECTION PROTOCOL

Specification	MIB-5141SV
IMAGE SENSOR	1 / 1.8 "CMOS
ELECTRONIC SHUTTER	1/25S~ 1/100000S
MIN. ILLUMINATION	COLOR: 0.00Lux@F1.2, AGC ON, B/W: 0Lux WITH IR
LENS	3.6-10mm VARIFOCAL LENS
VIDEO COMPRESSION	H.265 MP, H.264 BL/MP/HP, MJPEG
AUDIO COMPRESSION	G.711A / G.711U
BIT-RATE	64Kbps ~ 10Mbps
ENCODE MODE	VBR / CBR
IMAGE QUALITY	FIVE LEVELS UNDER VBR;FREELY ADJUSTABLE UNDER CBR
RESOLUTION	5MP (2592×1944), 2K (2560×1440), 1080P(1920×1080), 720P(1280×720), D1, CIF, 480x240
MULTI-STREAM	5MP(1~30fps) / 2K(1~30fps) / 1080P(1~30fps) / 720P(1~30fps) / 720P(1~5fps) / D1(1~10fps) / CIF(1~30fps) / D1(1~30fps) / CIF(1~30fps) / 480x240(1~30fps)
IMAGE SETTINGS	ROI,SATURATION, BRIGHTNESS, HUE, CONTRAST, WDR, SHARPNESS, DNR, ETC
NETWORK	RJ45
VIDEO OUTPUT	CVBS (BNC × 1)
AUDIO	TWO-WAY AUDIO(MIC IN × 1, MIC OUT × 1)
CARD STORORAGE	TF CARD, UP TO 64GB
RS485	× 1
ALARM INPUT/OUTPUT	× 1 / x1
REMOTE MONITORING	BROWSER, CMS, MOBILE APP
SUPPORTED BROWSERS	IE / CHROME / FIREFOX / SAFARI
ONLINE CONNECTION	10 ONLINE USERS
PROTOCOL	TCP/IP, UDP, DHCP, NTP, RTSP, PPPOE, DDNS, SMTP, FTP
STORAGE	LOCAL STORAGE (TF CARD), NETWORK REMOTE STORAGE
SMART ALARM	MOTION ALARM, SENSOR ALARM
INTELLIGENT ANALYSIS	PEA / OSC / AVD
WATER-PROOF	IP66
POWER SUPPLY	DC 12V/PoE
IR CONSUMPTION	< 3W / < 7.5W w/ IR on
OPERATING TEMP	-20°C ~ 50°C, 10% ~ 90% HUMIDITY
DIMENSIONS	F109mm × 284mm
WEIGHT	1132g