

OPTICOM**MIP-4002****2.1MP IP Outdoor PTZ Camera w/ IR**

Features

4.7mm ~ 94.0mm(20×)OPTICAL ZOOM
 8 IR LEDs
 H.264 Dual Streaming
 6 High Power LEDs / 300ft Distance
 DWDR, 2D / 3D DNR, AWB, AGC, BLC

More Features

SUPPORT P2P
 PENETRATION,
 MOBILE PHONE
 PUSH ALARM
 FUNCTION

MULTIPLE NETWORK
 MONITORING: WEB
 VIEWER, CMS &
 MOBILE

MAX 240°/S PAN
 SPEED, 360°
 ENDLESS PAN
 ROTATION

UP TO 255 PRESETS,
 8 AUTO SCAN, 8
 TOUR, 4 PATTERN

IR LEDS UP TO 120m

WITH ALUMINUM
 WIPER, AVOID DUST,
 ENSURE THAT THE
 IMAGE IS CLEAR

WATER PROOF
 (IP66), -35~55°C

DC 12V / AC 24V

Specification	MIP-4002
IMAGE SENSOR	1/2.9" 2.0 MEGAPIXEL SONY CMOS
EFFECTIVE PIXELS	1920(H)×1080(V)
SCANNING SYSTEM	PROGRESSIVE
ELECTRONIC SHUTTER SPEED	AUTO / MANUAL, 1/100~1/200,000S
MIN. ILLUMINATION	0.5 LUX (F1.6, 50 IRE, ICR OFF), 0.095 LUX (F1.6, 50 IRE, ICR ON)
PRIVACY MASKING	UP TO 5 AREAS
FOCAL LENGTH	4.7mm ~ 94.0mm (20× OPTICAL ZOOM)
MAX APERTURE	F1.6 ~ F3.5
FOCUS CONTROL	AUTO / MANUAL // AUTO / MANUAL
ANGLE OF VIEW	H: 55.2°~3.2°
PAN/TILT RANGE	PAN: 0° ~ 360° ENDLESS; TILT: -5° ~ 90°, AUTO FLIP 180°
MANUAL CONTROL SPEED	PAN: 0.01° ~120° /S; TILT: 0.01° ~100° /S
PRESET SPEED	PAN: 240° /S; TILT: 200° /S
PROTOCOL	PELCO_P, PELCO_D
PRESET POINT	256PCS
CRUISE SCAN	8 GROUPS, 32PCS PRESET EACH GROUP
AUTO SCAN	8 GROUPS, LEFT AND RIGHT BOUNDARY CAN BE SET, THE SCANNING SPEED CAN BE SET
PATTERN SCAN	4PCS, MAX 500PCS ORDER OR 30MINS EACH GROUP
WIPER FUNCTION	SUPPORT
COMPRESSION	H.264
RESOLUTION	1080P(1920×1080) / 720P(1280×720) / SVGA(800×600)
FRAME RATE	MAIN STREAM : 1080P / 720P / SVGA (1 ~ 25/30FPS) SUB STREAM : D1 / CIF / QCIF (1 ~ 25/30FPS)
BIT RATE	16K ~ 8192Kbps
ETHERNET	RJ-45 (10/100BASE-T)
PROTOCOL	IPV4/IPV6, HTTP, SSL, TCP/IP, UDP, UPNP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP
ONVIF	ONVIF VER. 2.0
MAX. USER ACCESS	10 USERS
SMART PHONE	IPHONE, IPAD, ANDROID
POWER SUPPLY	DC12V, 3A
POWER CONSUMPTION	< 50W
OPERATING TEMP	-22°F ~ 122°F, 10%~85%
DIMENSIONS	(W)210×(H)304mm / (W)8.2×11.9(H)inch