



MIV-4131SV

4 MP H.265 IR OUTDOOR DOME



Features

- 3.6mm Fixed
- 24 LEDs / 60ft Distance
- ICR Auto Switch
- DWDR
- 2D / 3D DNR

More Features

3D DNR, DIGITAL WDR

ROI CODING

SUPPORT LOCAL CVBS VIDEO OUTPUT AND ONE-WAY AUDIO

SUPPORT HARDWARE RESET

SUPPORT POE POWER SUPPLY

SUPPORT SMART PHONE, IPAD, REMOTE MONITORING SUPPORT P2P

IP66 & IK10 INGRESS PROTECTION

SUPPORT THREE STREAMS

IP66 RATED

Specification	MIV-4131SV
IMAGE SENSOR	1 / 3" CMOS
EFFECTIVE PIXELS	2688 x 1520
ELECTRONIC SHUTTER	1 / 25S ~ 1 / 100000S
MIN. ILLUMINATION	COLOR: 0.05Lux@F1.2, AGC ON, B/W: 0Lux WITH IR
LENS	3.6mm FIXED LENS
BLC	YES
VIDEO COMPRESSION	H.265 MP, H.264 BL/MP/HP, MJPEG
AUDIO COMPRESSION	G.711A / G.711U
BIT-RATE	64Kbps ~ 10Mbps
ENCODE MODE	VBR / CBR
IMAGE QUALITY	FIVE LEVELS UNDER VBR;FREELY ADJUSTABLE UNDER CBR
RESOLUTION	4MP(2560X1440), 3MP(2304x1296), 1080P(1920x1080), 720P(1280x720), D1, CIF, 480x240
MULTI-STREAM	4MP(1~30fps)/ 3MP(1~30fps)/ 1920x1080(1~30fps)/ 720P(1~30fps) 720P(1~30fps)/ D1(1~30fps)/ CIF(1~30fps)D1(1~30fps)/ 480x240(1~30fps)/ CIF(1~30fps)
IMAGE SETTINGS	ROI,SATURATION, BRIGHTNESS, HUE, CONTRAST, WDR, SHARPNESS, DNR, ETC
NETWORK	RJ45
VIDEO OUTPUT	CVBS (BNC x 1)
AUDIO	ONE-WAY AUDIO(MIC IN x 1)
REMOTE MONITORING	BROWSER, CVMS, MOBILE CVMS
SUPPORTED BROWSERS	IE / CHROME / FIREFOX / SAFARI
ONLINE CONNECTION	10 ONLINE USERS
PROTOCOL	TCP/IP, UDP, DHCP, NTP, RTSP, PPPOE, DDNS, SMTP, FTP
CONNECTION PROTOCOL	ONVIF
STORAGE	NETWORK REMOTE STORAGE
SMART ALARM	MOTION ALARM
INTELLIGENT ANALYSIS	PEA / OSC / AVD
ANGLE ADJUSTMENT	HORIZONTAL: 0°~68°,VERTICAL: 0°~220°,ROTATION: 0°~240°
POWER SUPPLY	DC 12V/PoE
IR CONSUMPTION	< 2.5W / < 4W w/ IR on
WORKING ENVIRONMENT	-22°F ~ 122°F, 10% ~ 90% HUMIDITY
DIMENSIONS	F166mm x 91mm
WEIGHT (NET)	605g