



## Features

3.3-12mm Varifocal  
30 LEDs / 100ft Distance  
ICR Auto Switch  
S-WDR  
2D / 3D DNR

### More Features

3D DNR, S-WDR

SUPPORT AUTO ZOOM  
AND MANUAL ZOOM

ROI CODING

SUPPORT LOCAL CVBS  
VIDEO OUTPUT AND  
TWO-WAY AUDIO

SUPPORT POE POWER  
SUPPLY

SUPPORT SMART  
PHONE, IPAD, REMOTE  
MONITORING

SUPPORT P2P

IP66 & IK10 INGRESS  
PROTECTION

SUPPORT THREE  
STREAMS

IP66 RATE

BACKLIGHT  
COMPENSATION

Specification	MIV-4141SV
IMAGE SENSOR	1 / 3" CMOS
ELECTRONIC SHUTTER	1 / 25S ~ 1 / 100000S
MIN. ILLUMINATION	COLOR: 0.05Lux@F1.2, AGC ON, B/W: 0Lux WITH IR
LENS	3.3-12mm VARIFOCAL LENS
VIDEO COMPRESSION	G.711A / G.711U
AUDIO COMPRESSION	64Kbps ~ 10Mbps
BIT-RATE	VBR / CBR
ENCODE MODE	FIVE LEVELS UNDER VBR;FREELY ADJUSTABLE UNDER CBR
IMAGE QUALITY	4MP(2560X1440), 3MP(2304x1296), 1080P(1920x1080), 720P(1280x720), D1, CIF, 480x240
RESOLUTION	4MP(1~30fps)/ 3MP(1~30fps)/ 1920X1080(1~30fps)/ 720P(1~30fps) 720P(1~30fps)/ D1(1~30fps)/ CIF(1~30fps)
MULTI-STREAM	D1(1~30fps)/ 480x240(1~30fps)/ CIF(1~30fps)
IMAGE SETTINGS	ROI,SATURATION, BRIGHTNESS, HUE, CONTRAST, WDR, SHARPNESS, DNR, ETC
NETWORK	RJ45
VIDEO OUTPUT	CVBS (BNC x 1)
AUDIO	TWO-WAY AUDIO(MIC IN x 1, MIC OUT x 1)
CARD STORAGE	TF CARD, UP TO 64GB
RS485	x 1
ALARM INPUT/OUTPUT	x 1 / x 1
REMOTE MONITORING	BROWSING,CVMS,MOBILE CVMS
SUPPORTED BROWSERS	IE / CHROME / FIREFOX / SAFARI
ONLINE CONNECTION	10 ONLINE USERS
PROTOCOL	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
CONNECTION PROTOCOL	ONVIF
STORAGE	LOCAL STORAGE (TF CARD), NETWORK REMOTE STORAGE
SMART ALARM	MOTION ALARM, SENSOR ALARM
INTELLIGENT ANALYSIS	PEA / OSC / AVD
ANGLE ADJUSTMENT	HORIZONTAL: 0°~77°,VERTICAL: 0°~360°,ROTATION: 0°~360°
POWER SUPPLY	DC 12V/PoE
IR CONSUMPTION	< 2.5W / < 5W w/ IR on
OPERATING TEMP	-22°F ~ 122°F, 10% ~ 90% HUMIDITY
DIMENSIONS	F150mm x 114mm
WEIGHT (NET)	1260g