

OPTICOM**MIV-5151SV****4 MP H.265 IR OUTDOOR DOME CAMERA**

Features

3.6-10mm Varifocal
 30 LEDs / 100ft Distance
 ICR Auto Switch
 S-WDR
 2D / 3D DNR

More Features

SUPPORT 8 ROI
 CODING ONE GIGABIT
 ETHERNET NETWORK
 PORT, 10M / 100M /
 1000M SELF-
 ADAPTIVE

SUPPORT SD CARD
 LOCAL STORAGE, UP
 TO 128GB

SUPPORT CVBS
 LOCAL VIDEO, TWO-
 WAY AUDIO AND POE
 POWER SUPPLY

SUPPORT SMART
 PHONE, IPAD,
 REMOTE MONITORING

SUPPORT P2P

IP66 & IK10 INGRESS
 PROTECTION

SUPPORT THREE
 STREAMS

BACKLIGHT
 COMPENSATION

IP66 RATED

Specification	MIV-5151SV
IMAGE SENSOR	1 / 1.8" CMOS
ELECTRONIC SHUTTER	1 / 25S ~ 1 / 100000S
MIN. ILLUMINATION	COLOR: 0.00Lux@F1.2, AGC ON, B/W: 0Lux WITH IR
LENS	3.6-10mm VARIFOCAL LENS
VIDEO COMPRESSION	H.265 MP, H.264 BL/MP/HP, MJPEG
AUDIO COMPRESSION	G.711A / G.711U
BIT-RATE	64Kbps ~ 10Mbps
ENCODE MODE	VBR / CBR
IMAGE QUALITY	FIVE LEVELS UNDER VBR; FREELY ADJUSTABLE UNDER CBR
RESOLUTION	5MP (2592×1944), 2K (2560×1440), 1080P(1920×1080), 720P(1280×720), D1, CIF, 480x240
MULTI-STREAM	5MP(1~30fps) / 2K(1~30fps) / 1080P(1~30fps) / 720P(1~30fps) 720P(1~5fps) / D1(1~10fps) / CIF(1~30fps) D1(1~30fps) / CIF(1~30fps) / 480x240(1~30fps)
IMAGE SETTINGS	ROI, SATURATION, BRIGHTNESS, HUE, CONTRAST, WDR, SHARPNESS, DNR, ETC
NETWORK	RJ45
VIDEO OUTPUT	CVBS (BNC × 1)
AUDIO	TWO-WAY AUDIO(MIC IN × 1, MIC OUT × 1)
CARD STORAGE	TF CARD, UP TO 64GB
RS485	× 1
ALARM INPUT/OUTPUT	× 1 / × 1
REMOTE MONITORING	BROWSING, CVMS, MOBILE CVMS
SUPPORT BROWSERS	IE / CHROME / FIREFOX / SAFARI
ONLINE CONNECTION	10 ONLINE USERS
PROTOCOL	TCP/IP, UDP, DHCP, NTP, RTSP, PPPOE, DDNS, SMTP, FTP
CONN PROTOCOL	ONVIF
STORAGE	LOCAL STORAGE (TF CARD), NETWORK REMOTE STORAGE
SMART ALARM	MOTION ALARM, SENSOR ALARM
INTELLIGENT ANALYSIS	PEA / OSC / AVD
ANGLE ADJUSTMENT	HORIZONTAL: 0°~77°, VERTICAL: 0°~360°, ROTATION: 0°~360°
POWER SUPPLY	DC 12V/PoE
IR CONSUMPTION	< 3W / < 5.5W w/ IR on
OPERATING TEMP	-22°F ~ 122°F, 10% ~ 90% HUMIDITY
DIMENSIONS	F150mm × 114mm
WEIGHT (NET)	1025g