

8 Channel Camera Kit



Specifications:

DVR Specifications

- Supports 8 Cameras
- 8 BNC Video Inputs
- BNC Video Output and VGA output
- 4 Alarm Inputs / 1 Alarm Output
- MPEG-4 Compression
- NTSC 352x240/CH: MAX. 120fps/8CH & 704x480/CH: MAX. 30fps/4CH
- Record Modes: Continuous / Schedule / Motion / Sensor / Manual
- Record Quality: Low / Medium / High
- Triplex Operations: Record, Playback, Network
- Network: Dynamic IP, LAN
- Networking Functions: Live, Search, Playback, PTZ Control, Backup, Setup
- Back up via the Network or USB Thumb Drive (Still image & Video Data)
- Power Source: DC 12V adapter (included)
- Operating Temperature: +41° ~ +104°F / +5° ~ +41° C
- Humidity: 30%~90%
- Dimensions: 9.6" x 12" x 2.4" / 245W x 304D x 60H mm

*100ft Cables Included
 ** Mix and Match Cameras

Camera Specifications

- 1/3" Sony Super HAD CCD
- IR Bullet Camera 480 TV Lines / Dome Camera 420 TV Lines
- Internal Synchronization
- Sensitivity: 0.3 lux (Bullet Camera 0 lux w/ IR ON)
- S/N Ratio: More Than 45dB
- Gamma Characteristic: 0.45
- Video Output: 1.0Vp-p75ohm
- Electronic Shutter: 1/60sec ~ 1/100,000sec
- Power Source: DC 12V Distributed Power Supply (included)
- Operation Temperature: +14° to +122°F / -10° to +50° C

