

Outdoor Pressurized Speed Dome

Features

- Enhanced Die-Cast Aluminum Construction - IP68
- Double Dome Housing
- Heater / Blower System Built-in
- Privacy Mask
- 256 Camera ID Addressable
- 360 Degree Pan Range / 90, 180 Degree Auto Flip
- Low Pressure Warning Alarm
- 128 Presets, 4 tracks, 40 seconds pattern Memory
- RS485 Communication, Cat5 Cable, Multi-Protocol Supported



Specifications

Model	PT509Z-22	PT509Z-30	PT509Z-36
Image Sensor		1/4" Sony Super HAD	
Effective Pixels	795 x 596	811 x 508	
Synchronization		Internal	
Video Out		1.0Vp-p (75 OM, composite)	
White Balance	5 Steps: Auto / Push Auto / Outdoor / Indoor / Special		
Resolution		480TVL	
S/N Ratio	>48dB	>48dB	>50dB
Electric Shutter	1/50-10,000	1/50-10,000	1-1/10,000
Min. Illumination	0.001 Lux	0.001	0.01
BLC	Auto	9 Zones	9 Zones
Focal Length	F 3.9-85.8mm	F 3.3-99mm	F 3.4-122.4mm
Max. Zoom	220X	300X	432X
Camera OSD	On / Off	On / Off	No
Gain		Auto / Manual	
Pan Preset Speed		300 Degrees / S	
Tilt Preset Speed		120 Degrees / S	
Privacy Masking	No	No	Yes
WDR	No	No	Yes
DSS & SensUp	Yes	Yes	No
Operational Temp	-31 to +140 Degrees Fahrenheit / -35 to +60 Degrees Celsius		
Power	24VAC, 20VA		
Weight		17.64 lb / 8 kg	