

## Wireless Transmitter/Receiver

4 Mile Range

### Features

- Easy to Install and Operate
- 8 User Selectable Channels
- No Interference from 802.11 b/g Data Networks
- Rugged All Weather IP-67 Rated
- Up to 4 Mile Range
- Delivers High Resolution, Real-Time Video
- Wall or Pole Mount Bracket Included
- One Year Limited Warranty

### Specifications

- Operating Frequency: 5.725 GHz - 5.875 GHz
- Radiated Power: 50 mV/M @ 3M
- Operating Distance Line of Sight: Up to 4 Miles
- Video Format: NTSC / PAL
- Antenna Type: Tx: 3dB Internal Fixed Directional, Rx: 29dB External Parabolic Dish
- Antenna Connector: SMA Female
- Video Connector Format: BNC Female
- Video Impedance & Level: 75 Ohms @ 1 Volt Peak to Peak
- Audio Connector Format: BNC Female
- Audio Impedance & Level: 600 Ohms @ 1 Volt Peak to Peak
- Receiver Sensitivity: -84dBm
- FCC / IC / CE Approved
- Operating Voltage: 9 - 14 Volts DC, Polarity Protected
- Power Supply: Two PS-1250 (included)
- Power Consumption: Tx - 230 mA / Rx - 330 mA
- Operating Temperature: -40 to +170 Degrees Farenheit / -40 to +76 Degrees Celsius
- Dimensions: 7" x 7" x 4.5" / 177.8 x 177.8 x 114.3 mm
- Weight: 32 oz / .9 kg



Established in 1973