

Desktop Transmitter

1,000' Range

Features

- Easy to Install and Operate
- 8 User Selectable Channels
- Stereo Audio Transmission Capable
- Not susceptible to interference from 2.4GHz 802.11 devices
- Convenient Front Panel Frequency Selection
- Excellent for Portable, Temporary, and Covert Applications
- One Year Warranty



Specifications

- Operating Frequency: 5.725 GHz - 5.875 GHz
- Radiated Power: 50 mV/M @ 3M
- Operating Distance Line of Sight: Up to 1,000 feet with Optional Receiver
- Video Format: NTSC / PAL
- Antenna Type: Omni Directional Rubber Duck
- Antenna Connector: SMA Female
- Video Connector Format: BNC Female
- Video Impedance & Level: 75 Ohms @ 1 Volt Peak to Peak
- Audio Connector Format: One Left and One Right RCA Female
- Audio Impedance & Level: 600 Ohms @ 1 Volt Peak to Peak
- FCC / IC / CE Approved
- Operating Voltage: 8 - 32 Volts DC, Polarity Protected
- Power Supply: PS-1250 (included)
- Power Consumption: 140mA
- Operating Temperature: -22 to +150 Degrees Fahrenheit / -30 to +65 Degrees Celsius
- Dimensions: 7.4" x 4.2" x 1.2" / 188 x 106.6 x 30.5 mm
- Weight: 15.5 oz / 441g



Established in 1973