



VDC22X

22X Zoom Day/Night PTZ Camera



-Features-

- 23x Optical, 10x Digital Zoom
- Mechanical IR Cut Filter
- 480 TV Lines High Resolution
- Digital Slow Shutter (DSS)
- 128 Preset Positions
- Built-in Heater/Blower




Quick and Easy Installation

STEP 1: Fix the wall bracket to the wall & Disassemble the outdoor flange and dome housing.

STEP 2: Run the cable of the outdoor flange and connect the outdoor flange with the wall mount.

STEP 3: Mount the safety hanging lock to the dome housing and align the guide pins. Turn the housing to lock, and tighten screws to secure.



-Specifications-

VDC22X	
Sensor	1/4" Sony Super HAD CCD
Resolution	480 TV Lines
Illumination	0.03 Lux
Lens	3.9-85.8mm / F1.6~1.9
Sync System	Internal / External (V-Lock)
Video Out	1.0Vp-p, 75Ω
Zoom	230x
S/N Ratio	48dB
Picture Effect	Positive / Negative / Freeze / Cross Line / Mask Motion Detect / H/V Reverse
White Balance	Auto (ATW or AWB)
Auto Gain Control	Auto (24dB max)
AE Control	Auto / Fix
Back Light Compensation	On / Off Switchable
Pan	Range 360°, Speed 0.6-240°
Tilt	Range 0-100°, Speed 0.5-120°
Preset	128 Preset Positions
Auto Cruise	1 Auto Cruise Track
Power	AC24V
Power Consumption	2 Amps
Dimensions	7.9" x 13.2" / 200 x 336mm
Weight	9.9 lb / 4.5kg
Operating Temp	-22° ~ 122° F (-30° ~ 50° C)