

## HD-212-VD

Vandal Proof Dome



### -Features-

- 2.2M 1080P Full HD
- HD SDI
- Composite Video Output (750TVL)
- BT 1120 Digital Output
- Digital Zoom Max 32x
- Multi Protocol Support
- IP 67 Aluminum Diecasting Housing
- Intelligent Motion Detection

### HD-212-VD

Image Sensor	1/3" Panasonic CMOS
Total Pixels	2010(H) x 1108(V) = 2,227,080
Active Pixels	1944(H) x 1092(V) = 2,122,848
Scanning System	Progressive
Resolution	Digital: 1080p (30p), 720p (80p) / Analog: 750TVL
Min. Illumination	Color: 1.0 Lux, BW: 0 Lux. Color DSS: 0.002 Lux, BW DSS: 0 Lux
Video Output	Digital: BT 1120, HD-SDI / Analog: 1.0Vp-p (75 ohm, composite)
S/N Ratio	More than 50dB (AGC Off)
Gain Control	0~20
Shutter Speed	1/30 ~ 1/30,000 sec / 1/25 ~ 1/30,000 sec
Digital Shutter Speed	Off / x2 / x3 / x4
Brightness	0~20 Steps
WDR/BLC	Off/WDR/BLC
Day/Night	Auto/Ext/Day/Night
DNR	Off/Low/Middle/High
Mirror	Off/H/V/H+V
E Zoom	0~x32
Privacy Mask	Off/28 Positions
Motion Detection	Off/8 Positions
Comm.	Baud Rate: 2400 / 4800 / 9600 / 19200 / 38400 / 57600
	Protocol (Pelco P, Pelco D, Update)
Power Source	DC 12V
Power Consumption	250mA