

Underwater Bullet Camera CC06-HBU36F-K



Features

- 1/3" 960H SONY Super HAD II Sensor
- 700 TVL Resolution / 3.6mm Lens
- AISI 316 Stainless Steel Housing
- 15 Piece White LED Array
- Remotely Adjustable LED Control
- Corrosion / Bacteria Resistant
- Smart 3D-DNR / SENS-UP x8
- SS316 Bracket Included

20 Meter Urethane Extension
Cable Included



Specifications	CC06-HBU36F-K
Image Sensor	1/3" 960H SONY Super HAD II CCD
Effective Pixels	976 x 494
Resolution	700 TV Lines
Lens	3.6mm Fixed Lens
Scanning System	2:1 Interlaced
Sync System	Internal
S/N Ratio	More than 52dB
Video Output	1.0 Vp-p Composite Video, 75 Ohms
Illumination	0.1 Lux at F1.2 / 0.001 Lux with SENS-UP On
LED's	15 Piece White LED Array, Remotely Adjustable
Electronic Shutter	1/60~1/100,000 Sec.
SENS-UP	x8, Default
Gain Control	Automatic
Housing	AISI SS316 / IP68
Bracket	Included
Power	12V DC
Power Consumption	Max. 1.0w (160mA)
Operating Humidity	30% ~ 90%
Dimensions	49mm x 114mm / 1.93" x 4.49"
Operating Temperature	14°~122° F (-10°~50° C)
Weight	600g / 1.32 Lbs.