

LCDI-215IP, LCDI-24IP, LCDI-32IP

21.5", 24", 32" IP Ethernet Monitor



Features

- LED Backlight
- Full High Definition
- Mouse Included
- VESA Standard Mount
- ONVIF Protocol
- Metal Housing

More Features

Supports up to 5MP Cameras

Real-time Streaming Protocol

PTZ Support

Built-In Stand

Sequential

Supports TCP/IP, DHCP, DNS, HTTP, SMTP

H.264 Compression

Specification	LCDI-215IP	LCDI-24IP	LCDI-32IP
LCD Panel	21.5"	23.8"	32"
Viewable Area	476.6 x 268.1mm	527.04 x 294.16mm	698.4 x 392.8mm
Maximum Resolution	1920 x 1080		
Display Colors	16.7M		
Aspect Ratio	16:9		
Contrast Ratio	3000:1		
Response Time	1.3/3.7 ms	1.5/3.5 ms	6.5 ms
View Angle	89°/89°/89°/89°		
Input Video Signal	1 x HDMI, 1 x VGA, 1 x DVI-D, 2 x USB		
Audio	2 x RCA (R/L), 1 x Phone Jack, 3.5 Out		
Speaker	2 x Built-in Speaker (2 watt)		
IP Video Support	8x(1280*960)+sub(640-480)+4Ref.+1Play 8x(1920*1080)+sub(640-480)+2Ref.+1Play 8x(720*576)+sub(352-288)+2Ref.+8Play 8x(1280*720)+sub(640-360)+1Ref.+4Play 8x(1280*960)+sub(720*576)+2Ref.+1Play 8x(1920*1080)+sub(720*576)+4Ref.+1Play 4x(1920*1080)+sub(640-480)+4Ref.+1Play	25x(1280-960)+sub(720*576)+4Ref.+8Play 16x(2048-1536)+sub(960*576)+4Ref.+4Play 9x(2592*1944)+sub(960*576)+4Ref.+1Play	16x(1920*1080)+sub(960*576)+4Ref.+16Sub_Play/4Main_Play 16x(1280-960)+sub(960*576)+4Ref.+16Sub_Play/8Main_Play 9x(2048x1536)+sub(960*576)+4Ref.+9Sub_Play/4Main_Play 9x(2592-1944)+sub(960*576)+4Ref.+9Sub_Play/1Main_Play
OSD Settings	Yes		
Network Port	1 x RJ45, 10M/100M	1 x RJ45, 10M/100M/1000M	1 x RJ45, 10M/100M
Power Input	AC 100-240V 50/60Hz, Adapter DC 12V/5A		
Power Consumption	Approx. 24 watt	Approx. 27 watt	Approx. 58 watt
Dimensions	20.9 x 12.7 x 2.8"	23.1 x 13.9 x 2.43"	30 x 17.9 x 3.7"
VESA Pattern	75 x 75 / 100 x 100 / 200 x 200		100 x 100 / 200 x 200
Weight	12.6 lbs	12.8 lbs	29.1 lbs
Operating Temp	32° ~ 104°F (0° ~ 40°C)		