



LCDI-32IP, LCDI-42IP, LCDI-46IP, LCDI-55IP

32", 42", 46", 55" IP Ethernet Monitor



Features

- LED Backlight
- Full High Definition
- Mouse Included
- VESA Standard Mount
- ONVIF Protocol
- Metal Housing

More Features

Supports up to
5MP Cameras

Real-time
Streaming Protocol

PTZ Support

Built-In Stand

Sequential

Supports TCP/IP,
DHCP, DNS, HTTP,
SMTP

H.264 Compression

Specification	LCDI-32IP-16	LCDI-42IP-32	LCDI-46IP-32	LCDI-55IP-32
LCD Panel	32"	42"	46"	55"
Viewable Area	698.4 x 392.8mm	930.24x 523.26	1018.08 x 572.76	1209.6 x 680.4
Maximum Resolution	1920 x 1080			
Display Colors	16.7M			1073M
Aspect Ratio	16:9			
Contrast Ratio	3000:1	4000:1		
Response Time	6.5 ms	8ms		
View Angle	89°/89°/89°/89°			
Input Video Signal	1 x HDMI, 1 x VGA, 1 x DVI-D, 2 x USB			
Audio	2 x RCA (R/L), 1 x Phone Jack, 3.5 Out			
Speaker	2 x Built-in Speaker (2 watt)			
IP Video Support	16 x IP Video Streams	32 x IP Video Streams		
OSD Settings	Yes			
Network Port	1 x RJ45, 10M/100M			2 x RJ45, 10M/100M
Power Input	AC 100-240V 50/60Hz, Adapter DC 12V/5A			
Power Consumption	Approx. 58 watt	Approx. 78watt	Approx.107 watt	TBD
Dimensions	30 x 17.9 x 3.7"	39.2 x 23.2 x 3.3"	42.6 x 25.1 x 3.2"	TBD
VESA Pattern	100 x 100 / 200 x 200			
Weight	29.1 lbs	50.7 lbs	55.2	TBD
Operating Temp	32° ~ 104°F (0° ~ 40°C)			