

MIB-4131SV2

4 MP H.265 NETWORK IR BULLET CAMERA



Features

- 2.8mm Fixed Lens
- SMART IR / 100ft Distance
- True WDR
- 3D DNR
- Triple Streaming

More Features

- ICR Automatic Switching
- Smart IR Illumination
- True WDR
- 3D DNR, HLC, BLC, Defog and ROI encoding
- Supports Image Distortion Correction
- Built-in Micro SD Card Slot, up to 128GB
- DC12V/PoE Power Supply
- IP67 Ingress Protection
- P2P/NAT Function
- Intelligent Analytics Including:
 - Line Crossing
 - Region Intrusion
 - Person and Vehicle Counting
 - Scene Change
 - Vandalism Detection
 - Face Detection

Specification	MIB-4131SV2
Image Sensor	1 / 3" CMOS
Electronic Shutter	1 / 30S ~ 1 / 100000S
Min. Illumination	Color: 0.005Lux@F1.6, AGC On; 0 lux with IR, 0.0028 lux @F1.2, AGC ON; 0 lux with IR
Lens	2.8mm Fixed Lens
Video Compression	H.265 MP, H.264 BL/MP/HP, MJPEG
Audio Compression	G.711A / G.711U
Bit-Rate	64Kbps ~ 8Mbps
Encode Mode	VBR / CBR Adjustable
Max Image Resolution	2592 x 1520
Primary Stream	(2592 x 1520): 30fps 60Hz: (2592 x 1520, 2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720) @30fps HFR mode: (60Hz: 1920 x 1080, 1280 x 720) @ 60fps 50Hz: (2592 x 1520, 2560 x 1440, 2304 x 1296, 1920 x 1080, 1280 x 720) @25fps HFR mode: (50Hz: 1920 x 1080, 1280 x 720) @ 50Hz
Secondary Stream	(1280 x 720, 704 x 480, 352 x 288, 480 x 240) @ 30 fps
Tertiary Stream	(704 x 480, 352 x 288, 480 x 240) @ 30 fps
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc (Adjustable through Software or Browser)
Network	1 x RJ45 10M / 100M Self-Adaptation
Network Storage	Network Remote Storage
Audio	One-Way Audio(Mic In x 1); Compression: G711A / U
Remote Monitoring	Web Browser Interface, Mobile App, CVMS 2.0
Support Browsers	IE / Chrome / Firefox / Safari
Online Connection	10 Online Users
Protocol	UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS, IPv4, IPv6
Supported Protocol	ONVIF Profiles S and G
Smart Alarm	Motion Alarm, Sensor Alarm, SD Card Error, SD Card Full
Video	PEA / OSC / AVD
Waterproof	IP67
Power Supply	DC 12V/PoE
IR Consumption	<7.5W
Operating Temperature	-22°F ~ 122°F (-30°C~50°C), 10% ~ 90% Humidity
Dimensions	6.6" x 2.93" x 2.93" (167.5mm x 74.5mm x 74.5mm)
Weight	.93 lbs