



MIB-4151SV2

4MP IP Bullet Camera



Features

- H.265 Video Compression
- Up To 180 Feet At Night
- Motorized Varifocal Lens
- IP67 Ingress Protection
- Supports Triple Streaming

More Features

True Day/Night ICR
3D DNR, S-WDR (true)
BLC, HLC, Defog

Network Remote Storage,
Micro SD Card Storage

Smart Alarm – Motion
Detection, SD Card Error, SD
Card Full

Watermark, IP Address
Filtering, Video Mask,
Heartbeat, Password
Protection, Non-
photosensitive Switch,
Image Distortion Correction

Video Analytics: Perimeter
Protection – Line Crossing,
Region Entrance/Exiting/
Intrusion (human/motor
vehicle counting); Target
Counting – Line Crossing
Human/Motor Vehicle/Non-
Motor Vehicle Counting;
Exception Detection – Scene
Change, Video Blur and
Video Color Cast Detection;
Face Detection and Face
Capture

Specification	MIB-4151SV2
Sensor	1/3" CMOS
Image Size	2592 x 1520
Electronic Shutter	1/30s~1/100000s
Auto Iris	DC Iris
Min. Illumination	0.005 lux @ F1.4, AGC ON; 0 lux with IR,
Lens	Motorized 2.8~12mm @ F1.6
Day & Night	ICR
Video Compression	H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 / MJPEG
Resolution	4MP(2592 X1520), 2K (2560 x 1440), 3MP(2304x1296), 1080P(1920x1080), 720P(1280x720), D1, CIF, 480x240
Main-Stream	60Hz: 8MP(1~30fps)/1080P(1~30fps)/720P(1~30fps) 50Hz: 8MP(1~25fps)/1080P(1~25fps)/720P(1~25fps)
Sub-Stream	720P / D1 / CIF / 480x240 (60Hz: 1 ~ 30fps; 50Hz: 1 ~ 25fps)
Third Stream	D1 / CIF / 480x240 (60Hz: 1 ~ 30fps; 50Hz: 1 ~ 25fps)
Bit Rate	64Kbps~8Mbps
Bit Rate Type	VBR/CBR
Quality	Five Levels Under VBR, Freely Adjustable under CBR
Image Setting	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. Adjustable Through Client Software or Web Browser
Audio Compression	G711A/U
ROI	Each ROI to be Configured Separately
Network	RJ45 x 1
Audio	1 CH Audio In
Video Output	No
Remote Monitoring	IE Browsing, CMS Remote Control
Online Connections	Supports Simultaneous Streaming for up to ten users
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS
Interface Protocol	ONVIF
Power Supply	DC 12V/PoE IEEE802.3af
Power Consumption	<4.5W (IR ON: <8W)
Operating Temperature	-22°F~140°F (-30°C~60°C)
Dimensions	8.59" x 3.13" x 2.77" (218.1mm x 79.5mm, 70.4mm)
Weight	1.54lbs (.70kg)