



MIB-8151SV

4K/8MP IP Bullet Camera



Features

- H.265 Video Compression
- Up To 180 Feet At Night
- Motorized Varifocal Lens
- IP66 Ingress Protection
- Supports Triple Streaming

More Features

- True Day/Night ICR
- 3D DNR, S-WDR (true)
- Video Analytics: Object Removal, Line Crossing Detection and Intrusion Detection
- Supports Defogging, HLC, BLC, Digital Image Stabilization and Image Correction for Various Situations
- MicroSD Card Local Storage, up to 128 GB
- Supports Hardware Reset
- Supports Smartphone, iPad, and Remote Monitoring
- Supports P2P Remote Connection

Specification	MIB-8151SV
Sensor	1/2.5" CMOS
Image Size	3840x2160
Electronic Shutter	1/25s~1/100000s
Auto Iris	Fixed Iris
Min. Illumination	0.01Lux @F1.2, AGC ON; Lux with IR
Lens	Motorized 3.3~12mm @F1.4, Horizontal View Angle: 97.5°~38.5°
Day & Night	ICR
Video Compression	H.265 MP; H.264 BP / MP / HP; MJPEG
Resolution	8.4MP (3840x2160), 1080P (1920x1080), 720P (1280x720), D1, CIF, 480x240
Main-Stream	60Hz: 8MP(1~30fps)/1080P(1~30fps)/720P(1~30fps) 50Hz: 8MP(1~25fps)/1080P(1~25fps)/720P(1~25fps)
Bit Rate	64Kbps~16Mbps
Encode Mode	VBR/CBR
Quality	Five Levels Under VBR, Freely Adjustable under CBR
Image Setting	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. Adjustable Through Client Software or Web Browser
Audio Compression	G711A/U
ROI	Each ROI to be Configured Separately
Network	RJ45 x 1, 10M/100M Self-Adaptation
Audio	MIC In x 1, MIC Out x 1
Video Input	CVBS (BNC x 1)
Video Input/Output	1CH/1CH
RS485	Yes
Remote Monitoring	IE Browsing, CMS Remote Control
Online Connections	Supports Simultaneous Streaming for up to ten users
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol	ONVIF, GB-T/28181-2011
Smart Alarm	Motion Alarm, Sensor Alarm
PTZ	RS485 x 1
PoE	Yes
Power Supply	DC 12V/PoE
Power Consumption	<4.5W (IR ON: <8W)
Operating Temperature	-4°F~122°F (-20°C~50°C)
Dimensions	4.29in*11.18in
Weight	2.45lbs (1.11kg)