

MIS-4131SV

4 MP H.265 IR EYEBALL CAMERA



Features

- 2.8mm Fixed
- 2 High Power LEDs / 100ft Distance
- ICR Auto Switch
- WDR
- 2D / 3D DNR



More Features

ROI Coding
 Support local CVBS Video Output and One-Way Audio
 Support Hardware Reset
 Support POE Power Supply
 Support Smart Phone iPad, Remote Monitoring, Support P2P
 IP66 * IK10 Ingress Protection
 Support 3 Streams
 Our IP cameras offer a complete set of input and output connectors for easy installation
 Built-in PoE (Power over Ethernet) Port
 DC 12V Power
 CVBS Analog BNC Out
 Audio In (MIC)

Specification	MIS-4131SV
Image Sensor	1 / 3" CMOS
Electronic Shutter	1 / 25s ~ 1 / 100000s
Min. Illumination	Color: 0.05Lux@F1.2, AGC ON, B/W: 0Lux WITH IR
Lens	2.8mm Fixed Lens
BLC	Yes
Video Compression	H.265 MP, H.264 BL/MP/HP, MJPEG
Audio Compression	G.711A / G.711U
Bit-Rate	64Kbps ~ 10Mbps
Encode Mode	VBR / CBR
Image Quality	Five Levels Under VBR; Freely Adjustable Under CBR
Resolution	4MP(2560x1440), 3MP(2304x1296), 1080P(1920x1080), 720P(1280x720), D1, CIF, 480x240
Multi-Stream	4MP(1~30fps)/ 3MP(1~30fps)/ 1920x1080(1~30fps)/ 720P(1~30fps) 720P(1~30fps)/ D1(1~30fps)/ CIF(1~30fps)D1(1~30fps)/ 480x240(1~30fps)/ CIF(1~30fps)
Image Setting	ROI, Saturation, Brightness, Hue, Contrast, WDR, Sharpness, DNR, ETC
Network	RJ45
Video Output	CVBS (BNC x 1)
Audio	One-Way Audio (MIC IN x 1)
Remote Monitoring	IE Browsing, CVMS, Mobile CVMS
Supported Browsers	IE / Chrome / Firefox / Safari
Online Connection	10 Online Users
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Connection Protocol	ONVIF
Storage	Network Remote Storage
Smart Alarm	Motion Alarm
Intelligent Analysis	PEA / OSC / AVD
Waterproof	IP66
Angle Adjustment	Horizontal: 0°~360°, Vertical: 0°~90°, Rotation: 0°~360°
Power Supply	DC12V/PoE
IR Consumption	< 2.5W / < 5.5W
Operating Temperature	-22°F ~ 122°F, 10% ~ 90% Humidity
Dimensions	3.43" x 4.25" (87mm x 108mm)
Weight (Net)	.73 lbs / 330g