

MIV-4131SV

4 MP H.265 IR OUTDOOR DOME



Features

- 3.6mm Fixed
- 24 LEDs / 60ft Distance
- ICR Auto Switch
- DWDR
- 2D / 3D DNR

More Features

- 3D DNR, Digital WDR
- ROI Coding
- Support Local CVBS Video Output and One-Way Audio
- Support Hardware Reset
- Support PoE Power Supply
- Support Smart Phone, Ipad, Remote Monitoring
- Support IP66 & IK10 Ingress Protection
- Support Three Streams
- IP66 Rated

Specification	MIV-4131SV
Image Sensor	1 / 3" CMOS
Effective Pixels	2688 x 1520
Electronic Shutter	1 / 25S ~ 1 / 10000S
Min. Illumination	Color: 0.05Lux@F1.2, AGC On, B/W: 0Lux With IR
Lens	3.6mm Fixed Lens
BLC	Yes
Video Compression	H.265 MP, H.264 BL/MP/HP, MJPEG
Audio Compression	G.711A / G.711U
Bit-Rate	64Kbps ~ 10Mbps
Encode Mode	VBR / CBR
Image Quality	Five Levels Under VBR; Freely Adjustable Under CBR
Resolution	4MP(2560x1440), 3MP(2304x1296), 1080P(1920x1080), 720P(1280x720), D1, CIF, 480x240
Multi-Stream	4MP(1~30fps)/ 3MP(1~30fps)/ 1920x1080(1~30fps)/ 720P(1~30fps) 720P(1~30fps)/ D1(1~30fps)/ CIF(1~30fps)D1(1~30fps)/ 480x240(1~30fps)/ CIF(1~30fps)
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, WDR, Sharpness, DNR, Etc.
Network	RJ45
Video Output	CVBS (BNC x 1)
Audio	One-Way Audio (Mic In x 1)
Remote Monitoring	Browser, CVMS, Mobile CVMS
Supported Browsers	IE / Chrome / Firefox / Safari
Online Connection	10 Online Users
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Connection Protocol	ONVIF
Storage	Network Remote Storage
Smart Alarm	Motion Alarm
Intelligent Analysis	PEA / OSC / AVD
Angle Adjustment	Horizontal: 0°~68°, Vertical: 0°~220°, Rotation: 0°~240°
Power Supply	DC 12V/PoE
IR Consumption	< 2.5W / < 4W w/ IR on
Working Environment	-22°F~-122°F (-30°C~-50°C), 10%~90% Humidity
Dimensions	6.53" x 3.58" (F166mm x 91mm)
Weight (NET)	1.33 lbs (605g)