

# MIV-4141SV

## 4 MP H.265 IR OUTDOOR DOME



### Features

- 3.3-12mm Varifocal
- 30 LEDs / 100ft Distance
- ICR Auto Switch
- S-WDR
- 2D / 3D DNR

#### More Features

- 3D DNR, S-WDR
- SUPPORT AUTO ZOOM AND MANUAL ZOOM
- ROI CODING
- SUPPORT LOCAL CVBS VIDEO OUTPUT AND TWO-WAY AUDIO
- SUPPORT POE POWER SUPPLY
- SUPPORT SMART PHONE, IPAD, REMOTE MONITORING
- SUPPORT P2P
- IP66 & IK10 INGRESS PROTECTION
- SUPPORT THREE STREAMS
- IP66 RATE
- BACKLIGHT COMPENSATION

Specification	MIV-4141SV
IMAGE SENSOR	1 / 3" CMOS
ELECTRONIC SHUTTER	1 / 25S ~ 1 / 100000S
MIN. ILLUMINATION	COLOR: 0.05Lux@F1.2, AGC ON, B/W: 0Lux WITH IR
LENS	3.3-12mm VARIFOCAL LENS
VIDEO COMPRESSION	H.265 / H.264 / MJPEG
AUDIO COMPRESSION	G.711A / G.711U
BIT-RATE	64Kbps ~ 10Mbps
ENCODE MODE	VBR / CBR
IMAGE QUALITY	FIVE LEVELS UNDER VBR; FREELY ADJUSTABLE UNDER CBR
RESOLUTION	4MP(2560X1440), 3MP(2304x1296), 1080P(1920x1080), 720P(1280x720), D1, CIF, 480x240
MAIN STREAM	4MP(1~30fps) / 3MP(1~30fps) / 1920X1080(1~30fps) / 720P(1~30fps) / 720P(1~30fps) / D1(1~30fps) / CIF(1~30fps)
MULTI-STREAM	D1(1~30fps) / 480x240(1~30fps) / CIF(1~30fps)
IMAGE SETTINGS	ROI, SATURATION, BRIGHTNESS, HUE, CONTRAST, WDR, SHARPNESS, DNR, ETC
NETWORK	RJ45
VIDEO OUTPUT	CVBS (BNC x 1)
AUDIO	TWO-WAY AUDIO(MIC IN x 1, MIC OUT x 1)
CARD STORAGE	TF CARD, UP TO 64GB
RS485	x 1
ALARM INPUT/OUTPUT	x 1 / x 1
REMOTE MONITORING	BROWSING, CVMS, MOBILE CVMS
SUPPORTED BROWSERS	IE / CHROME / FIREFOX / SAFARI
ONLINE CONNECTION	10 ONLINE USERS
PROTOCOL	TCP/IP, UDP, DHCP, NTP, RTSP, PPPOE, DDNS, SMTP, FTP
CONNECTION PROTOCOL	ONVIF
STORAGE	LOCAL STORAGE (TF CARD), NETWORK REMOTE STORAGE
SMART ALARM	MOTION ALARM, SENSOR ALARM
INTELLIGENT ANALYSIS	PEA / OSC / AVD
ANGLE ADJUSTMENT	HORIZONTAL: 0°~77°, VERTICAL: 0°~360°, ROTATION: 0°~360°
POWER SUPPLY	DC 12V/PoE
IR CONSUMPTION	< 2.5W / < 5W w/ IR on
OPERATING TEMP	-22°F ~ 122°F, 10% ~ 90% HUMIDITY
DIMENSIONS	F150mm x 114mm
WEIGHT (NET)	1260g