

MIV-4151SV

4 MP H.265 IR OUTDOOR DOME CAMERA



Features

- H.265 COMPRESSION
- ICR AUTO SWITCH, TRUE DAY/NIGHT
- 2D/3D DNR, S-WDR
- IP66 & IK10
- IR CUT FILTER

More Features

ENCODE MODE – FIVE LEVELS UNDER VBR: FREELY ADJUSTABLE UNDER CBR

CARD STORAGE- TF CARD, UP TO 64GB

REMOTE MONITORING- BROWSER, CVMS, MOBILE CVMS

SUPPORT BROWSERS- IE, CHROME, FIREFOX, SAFARI

STORAGE- LOCAL STORAGE(TF CARD), NETWORK REMOTE STORAGE

IR DISTANCE- 100FT

Specification	MIV-4151SV
IMAGE SENSOR	1 / 3" CMOS
EFFECTIVE PIXELS	2688 X 1520
ELECTRONIC SHUTTER	1/255~1/100000S
MIN. ILLUMINATION	COLOR:0.05Lux@F1.2, AGC ON, B/W: 0Lux with IR
LENS	3.3-12mm MP MOTORIZED AUTO-FOCUS LENS (ICR)
LENS ANGLE / MOUNT	HORIZONTAL:50°, 80°-38°(-FZ) / CS MOUNT, 014 MOUNT (-FZ)
VIDEO COMPRESSION	H.265 MP, H264 BL/MP/HP, MUPEG
AUDIO COMPRESSION	G.711A/G.711U
BIT RATE	64Kpbs – 10Mbps
IMAGE QUALITY	4MP(2560 x 1440), 3MP(2304 x 1296), 1080P(1920 x 1080), 720P(1280 x 720), D1, CIF, 480 x 240
RESOLUTION	4MP(1-30fps), 3MP(1-30fps), 1920 x 1080(1-30fps) 720P(1-30fps), D1(1-30fps), CIF(1-30fps)
MULTI-STREAM	D1(1-30fps), 480 x 240(1-30fps), CIF(1-30fps)
IMAGE SETTING	ROI, SATURATION, BRIGHTNESS, HUE, CONTRAST, WDR, SHARPNESS, DNR, ETC
NETWORK	RJ45
VIDEO OUTPUT	CVBS (BNC x 1)
AUDIO	TWO-WAY AUDIO (MIC IN x 1, MIC OUT x 1)
RS485	x1
ALARM INPUT/OUTPUT	x1 / x1
ONLINE CONNECTION	10 ONLINE USERS
PROTOCOL	TCP/IP, UDP, DHCP, NTP, RTSP, PPPOE, DDNS, SMTP, FTP
CONN PROTOCOL	ONVIF
SMART ALARM	MOTION ALARM, SENSOR ALARM
INTELLIGENT ANALYSIS	PEA/OSC/AVD
IR LED-COUNT	30(05 12 mil)
WATERPROOF	IP66
ANGLE ADJUSTMENT	HORIZONTAL:0° - 77°, VERTICAL:0° - 360°, ROTATION:0° - 360°
POWER SUPPLY	DC12V/POE
POWER CONSUMPTION	<2.5W (IR OFF) / <5W (IR ON)
WORKING ENVIRO.	-22°F – 122°F, 10% - 90% HUMIDITY
DIMENSION	50mm x 114mm
WEIGHT	1260g