

MIV-5131SV4

5 MP H.265 IR OUTDOOR DOME



Features

- 5 Megapixel Vandal Dome
- Smart IR/ 100ft Night Vision Distance
- H.265 / H.264 / MJPEG
- Triple Stream support
- IP67 / IK10 Rated

More Features

- 5 Megapixel Support
- Max Resolution (2560 x 1920)
- ICR auto Switch
- True Day & Night vision
- 100ft. IR Night Vision
- IP 37 & IK10 Ingress Protection rated
- Support triple Stream
- Intelligent Analytics
- Web Interface & CMS and Mobile app Support
- Defog Support
- ADR, AWB, HLC, BLC, VCA
- 12V DC / PoE Power Support

Specification	MIV-5131SV4
Image Sensor	1 / 3" CMOS
Effective Pixels	2688 x 1520
Electronic Shutter	1 / 25S ~ 1 / 100000S
Min. Illumination	Color: 0.05Lux@F1.2, AGC On, B/W: 0Lux With IR
Lens	2.8mm Fixed Lens
BLC	Yes
Video Compression	H.265 MP, H.264 BL/MP/HP, MJPEG
Audio Compression	G.711A / G.711U
Bit-Rate	64Kbps ~ 10Mbps
Encode Mode	VBR / CBR
Image Quality	Five Levels Under VBR; Freely Adjustable Under CBR
Resolution	5MP (2560x1920) 4MP (2560x1440) 3MP (2304x1296) 1080P(1920x1080) 720P (1280x720), D1, CIF, 480x240
Multi-Stream	5MP / 4MP / 3MP / 1920x1080 / 720P(1~30fps) 720P / D1 / CIF/ 480x240 (1~30fps)
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, WDR, Sharpness, DNR, Etc.
Network	RJ45
Video Output	CVBS (BNC x 1)
Audio	One-Way Audio (Mic In x 1)
Remote Monitoring	Browser, CVMS, Mobile CVMS
Supported Browsers	IE / Chrome / Firefox / Safari
Online Connection	10 Online Users
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPOE, DDNS, SMTP, FTP
Connection Protocol	ONVIF
Storage	Network Remote Storage
Smart Alarm	Motion Alarm
Intelligent Analysis	PEA / OSC / AVD
Angle Adjustment	Horizontal: 0°~68°, Vertical: 0°~220°, Rotation: 0°~240°
Power Supply	DC 12V/PoE
IR Consumption	< 2.5W / < 4W w/ IR on
Working Environment	-22°F~122°F (-30°C~50°C), 10%~90% Humidity
Dimensions	6.53in x 3.58in (F166mm x 91mm)
Weight (NET)	1.33 lbs (605g)