



SVD-2400

Silver Series Hybrid DVR (4/8/16 Channel)

Features



H.264 High Profile Compression
 BNC, HDMI & VGA Output
 2 Way Audio
 720p / 1080p
 Hybrid HD-TVI / Analog / AHD

More Features

Mobile App
"Super Live Pro"
 Multi Screen Viewing
 Record
 Snapshot
 PTZ Control
 Save Device List

Specification	SVD-2404	SVD-2408	SVD-2416
System CPU	Cortex A9		
System OS	Embedded Linux		
Video Input	4 BNC + 1 IP (CHS)	8 BNC + 1 IP (CH.9-12)	16 BNC + 1 IP (CH.17-24)
Resolution	1080P (1920*1080),720P(1280*720),(960*480)		
Frame Rate	720P 480FPS (NTSC) 400FPS (PAL)		
	1080P 60FPS (NTSC)	1080P 120FPS (NTSC)	1080P 240FPS (NTSC)
Record Bitrate	1-6 MBPS		
Record Encode	VBR/CBR		
Record Quality	6 Level		
Record Mode	Manual, Timer, Motion		
File Manager	Lock, Unlock, Reserving Time		
Resolution	3MP/1080P/960P/720P/WD1/D1		
Frame Rate (FPS)	3MP:15FPS(NTSC), 1080P/960P/720P:30FPS(NTSC) Per Channel		
Playback	4 Channel / 8 Channel / 8 Channel		
Search	Time, Motion, Single Or Multi Channel		
Function	Play, Pause, FF,FB, Digital Zoom		
Alarm Mode	Motion, Video Loss		
Alarm In/Out	N / A		
Alarm Triggering	Record, PTZ Preset, E-Mail		
Interface	R145 10M/100M/1000M Ethernet Network Port		
Protocol	TCP, IP, UDP, DHCP, DNS, DONS		
Users	8 Users Online, Dual Stream		
HDD	SATA * 1 (Up To 8TB)		SATA * 2 (Up To 16TB)
RS485	RS 485 *1		
USB	USB 2.0*2, Mouse & Backup		
IR Controller	Remote Controller		
Power Supply	DC 12V, 2A	DC 12V, 3A	DC 12V, 4A
Consumption	<9W(Without HDD)	<14W(Without HDD)	<20W(Without HDD)
Dimension	10l x 12w x 2"h / 254 x 304.8 x 50.8mm		2.7 x 17.3 x 15.3" (up to 32GBHDD) / 3.5 x 16.9 x 17.7" (Over 32GB HDD)
Operating Temperature	50°F~122°F (10°C~50°C), 10% -90% Humidity		