

**SVD-2432****Silver Series Hybrid DVR (32 Channel)**

## Features



H.264 High Profile Compression  
 HDMI & VGA Output  
 2 Way Audio  
 720p / 1080p  
 Hybrid HD-TVI / Analog / AHD

### More Features

Mobile App  
**"Super Live Pro"**  
 Multi Screen Viewing  
 Record  
 Snapshot  
 PTZ Control  
 Save Device List

Specification	SVD-2432
System CPU	Cortex A9
System OS	Embedded Linux
Input	32 BNC (NO IP)
Input / Output	RCA *1/RCA *1
Resolution	1080P (1920 *1080),720P(1280*720),(960*480)
Frame Rate	720P 960FPS (NTSC) / 1080P 480FPS (NTSC)
Bitrate	1-6 MBPS
Encode	VBR/CBR
Quality	6 Level
Mode	Manual, Timer, Motion , Sensor
File Manager	Lock, Unlock, Reserving Time
Resolution	3MP/1080P/960P/720P/WD1/D1
Frame Rate (FPS)	3MP:15FPS (NTSC), 1080P/960P/720P:30FPS (NTSC) Per CH
Playback	8 CH
Search	Time/Calendar Search, Event (Motion, External Alarm)
Smart Search	Highlighted Date and Time to Display the Recorded Channels
Function	Play, Pause, FF, FB, Digital Zoom
Mode	Sensor, Motion, Video Loss
Input / Output	16 CH / 4 CH
Triggering	Record, PTZ Preset, Alarm Out, E-mail, Etc.
Interface	R145 10M/100M/1000M Adaptive Ethernet Network Port
Protocol	TCP, IP, UDP, DHCP, DNS, DNS
Users	10 Users Online, Dual Stream
HDD	SATA * 8 (Up to 64TB)
RS485	RS 485 *2
USB	USB 2.0*2, One for Mouse/ One for USB Backup
IR Controller	Remote Controller
Power Supply	ATX
Consumption	<40W (Without HDD)
Dimensions	16.9" w x 17.7" h x 3.5" d (430mm x 450mm x 89mm)
Operating Temperature	50°F~122°F (10°C~50°C) 10%~90% Humidity