

SVN-2500E Series

32/64 Channel H.265 4K NVR



Features

- 4K HDMI Output
- H.265 High Profile Compression Format
- Dual Stream Recording
- Includes IR Remote Controller

More Features

Remote Control via IE or CMS: Preview, Playback, Backup, PTZ and Configuration
 Dual Stream Technology for Local Storage with High Definition, Remote Network Transmission and Remote Surveillance with Mobile Device
 Multi-User Online Simultaneously (10 Max)
 Authorization Management, Log View and Device Status View
 4K Output, True High Resolution Display
 Support PTZ Preset and Auto Cruise, Up To 255 Presets and 8 Cruises
 Support NAT Function and QR Code Scanning by Mobile Phone and PAD
 1 x USB 2.0 (Front Panel), 1 x USB 3.0 (Rear Panel), 1 x USB 2.0 (Rear Panel – 64CH only)

Specification	SVN-2532E	SVN-2564E
Compression	Standard H.265 HEVC (High Efficiency Video Coding) & H.264	
OS	Embedded Linux	
Network Bandwidth	256Mbps	
Network Format	5MP / 4MP / 3MP / 1080P / 960P / 720P @ 25FPS / 30FPS	
Video Output	HDMI x 1: 4K / 1080P / 720P, HDMI x 1: 1080P / 720P VGA x 1: 1920 x 1080 / 1280 x 1024	HDMI x 2: 4K / 1080P / 720P, VGA x 1: 1920 x 1080 / 1280 x 1024
Audio Network Input	32 CH IPC Audio Input	64 CH IPC Audio Input
2-Way Audio	RCA *1	
Audio Local Output	RCA *1	
Record Resolution	5MP / 4MP / 3MP / 1080P / 960P / 720P	
Record Mode	Manual, Timer, Motion, Sensor	
Simultaneous Playback	Max. 16 CH	
Search	Time Slice / Time / Event / Tag Search	
Smart Search	Highlighted Color to Display the Camera Record in a Certain Period of Time, Different Colors Refer to Different Record Events	
Playback Function	Play, Pause, FF, FB, Digital Zoom, Etc.	
Alarm Mode	Manual, Sensor, Motion, Exception	
Alarm Input / Output	Support IPC Alarm Input / Output	8 CH Local Alarm Input, Support IPC Alarm Input / 4 CH Output
Alarm Triggering	Record, Snap, Preset, E-mail, Etc.	
Network Interface	RJ45 10 / 100 / 1000 Mbps x 1	RJ45 10 / 100 / 1000 Mbps x 2
PoE Port	RJ45 10 / 100 / 1000 Mbps x 1	RJ45 10 / 100 / 1000 Mbps x 2
Network Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPNP, NTP, SMTP	
Mobile OS	AVY Mobile CVMS (iOS, Android)	
HDD	SATA x 2, MAX. 8TB Per HDD	SATA x 8, e-SATA x 2, MAX. 8TB Per HDD
Local Backup	USB Flash Drive, U Disc (Express & Flexible Back Up)	
Network Backup	Yes (Express & Flexible Back Up)	
Power Supply	DC 12V	ATX
Consumption	≤ 5W (Without HDD)	
Dimension (WxHxD)	16.9 x 3.5 x 18.1" (429.26 x 88.9 x 459.74mm)	16.9 x 3.5 x 17.7" (429.26 x 88.9 x 449.58mm)
Operating Temperatures	-14°F~-122°F (-26°C~-50°C), 10%-90% Humidity	