

SVN-2500P Series

4-16 Channel H.265 NVR



Features

- Dual Stream Recording
- 8MP/5MP/4MP/3MP/1080P/960P/720P
- H.265 High Profile Compression
- Intuitive and User-Friendly GUI
- One Touch Flexible Backup

More Features

4K Output, True High-Resolution Display
 Pentaplex: Preview, Record, Playback, Backup and Remote Access
 Remote Control via IE or CMS: Preview, Playback, Backup, PTZ and Configuration
 iOS and Android Support
 Mobile Device
 Search: Time Slice / Time / Event / Tag Search
 Authorization
 Management, Log View and Device Status View
 Support PTZ Preset and Auto Cruise, Up To 255 Presets and 8 Cruises
 Support NAT Function and QR Code Scanning by Mobile Phone and PAD
 Alarm Triggering: Record, Snap, Present, E-mail, Etc.
 10 Multi Users Online Simultaneously
 HDD Storage SATA x 4
 Max. 6TB per HDD
 ONVIF IP Camera Support up to 8MP (4K)

	Specification	SVN-2504P4	SVN-2508P8	SVN-2516P16
System	Compression	Standard H.265 HEVC (High Efficiency Video Coding) & H.264		
	OS	Embedded Linux		
Video	Network Input	4 CH IPC Input	8 CH IPC Input	16 CH IPC Input
	Network Access Bandwidth	40Mbps	64Mbps	256Mbps
	Network Access Format	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P @ 25FPS / 30FPS		
	Output	HDMI x 1: 4K x 2K (3840 x 2160) / 1080P (1920 x 1080) / 720P (1280 x 1024), VGA x 1: 1920 x 1080 / 1280 x 1024		
Audio	Network Input	4 CH IPC Audio Input	8 CH IPC Audio Input	32 CH IPC Audio Input
	2-Way Audio	RCA *1		
Record	Local Output	RCA *1		
	Resolution	5MP / 4MP / 3MP / 1080P / 960P / 720P		
Playback	Mode	Manual, Timer, Motion, Sensor		
	Simultaneous Playback	Max. 4 CH	Max. 8 CH	Max. 16 CH
	Smart Search	Highlighted Color to Display the Camera Record in a Certain Period of Time, Different Colors Refers to Different Record Events		
Alarm	Function	Play, Pause, FF FB, Digital Zoon, Etc.		
	Mode	Manual, Sensor, Motion, Exception		
Network	Input / Output	Support IPC Alarm Input / Output		16 CH Local and IPC Alarm Input / 4 CH Output
	Interface	RJ45 10 / 100 Mbps x 1		
	PoE Port	RJ45 x 4	RJ45 x 8	RJ45 x 16
Backup	Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPNP, NTP, SMTP		
	Local Backup	USB Flash Drive, U Disc (Express and Flexible)		
Port	Network Backup	Yes, Express and Flexible		
	USB	USB 2.0 x 2 (Front Panel)		USB 2.0 x 1 (Front Panel), USB 3.0 x 1 (Rear Panel)
Physical	Remote Controller	Optional		Yes
	Power Supply	DC 48V		
	Consumption	≤ 5W (NO HDD)	≤ 10W (NO HDD)	≤ 30W (NO HDD)
	Dimension (WxHxD)	12" w x 2" h x 10" d (254 x 304.8 x 50.8mm)		17" w x 2.76" h x 15.4" d (440 x 390 x 70mm)
Operating Temperature		-14°F ~ 122°F (-25°C ~ 50°C), 10% ~ 90% HUMIDITY		