

Video Baluns**VB-HD-01, VB-HD-02, VB-HD-04****1 Channel Passive Video Baluns****VB-HD-01****VB-02**

6" Wired BNC
Connector for
Easy Installation

Transmit Video Up to 1,000 Feet Over CAT5

"HD" will support HDTV, CVI, AHD, Analog

Transmit Video Over Low Cost UTP Wire

One UTP (24-16AWG) Per Video Signal

Cost-effective, Point-to-Point Transmission

Built-in Surge Protection

Two Screw Terminals for UTP / BNC-M for Coax

DC Loop Resistance 52 Ohms Per 1,000 ft (18 ohms per 100m)

Input Impedance: 75 Ohms (BNC)

Operating Temperature: 14°~122° F (-10°~50° C°)

VB-HD-04

Transmit Video & Power
300 Feet Over CAT5

**1 Ch. Passive Video/Power Balun**

Transmit Video & Power Up to 300 Ft Over CAT5

Cost-effective, Point-to-Point Transmission

CAT5 for Video / BNC for Coax / 2.1mm Jack for

Power

Designed for Use with CCTV Cameras, Monitors,

Processors, DVR's & Other CCTV Equipment

Input Impedance: 75 Ohms (BNC)

Output Impedance: 100 Ohms (RJ45)

DC Loop Resistance 52 Ohms Per 1,000 ft (18 ohms per 100m)

Operating Temperature: 14°~122° F (-10°~50° C)

Dimensions: 1.6 x 0.8 x 0.83 in / 4.0 x 2.0 x 2.1 cm

Weight: 0.6 oz / 35 grams