



# LCDI-15A, LCDI-17A, LCDI-19A

## 15", 17", 19" CCTV Monitor



### Features

- VESA Standard Mounting Pattern
- LED Back Light
- Picture in Picture
- Remote Control Included

### More Features

- 3D De-interlace
- 3D Comb Filter
- OSD
- DC 12V Power Supply Included
- Audio In/Out
- Stand Included

Specification	LCDI-15A	LCDI-17A	LCDI-19A
LCD Panel	15" Diagonal	17" Diagonal	19" Diagonal
Viewable Area	304mm x 228mm	337.9mm x 270.3mm	376mm x 301mm
Max. Resolution	1024 x 768	1280 x 270.3	1280 x 1024
Display Colors	16.7 Million Colors		
Aspect Ratio	4:3	5:4	
Brightness	250 cd/m		
Contrast Ratio	600:1	1000:1	
Response Time	6/2 ms	3.8/1.2 ms	1.3/3.7 ms
View Angle (U/D/L/R)	80/80/80/80	80/80/85/85	75/85/85/85
Input Video Signal	1 x BNC In/Out, 1 x VGA, 2 x HDMI, 1 x USB		
Audio	1 x Audio In, 1 x Audio Out		
Filter Type	3D Comb Filter		
De-Interlace and Noise Reduction	3D De-Interlace		
Dimensions	14.1 x 11.2 x 2.6"	15.4 x 13.9 x 2.6"	17 x 14.1 x 2.7"
VESA Pattern	75 x 75mm / 100 x 100mm / 200 x 200mm		
Case and Stand Material	High Impact Plastic		
Weight	7.1 lbs	8.6 lbs	10.6lbs
Power Consumption	<18w	<20w	<22w
Power Input	AC 100-240V 50/60HZ, Adapter DC 12V/5A		
Operating Temperature	32° ~ 104° F (0° ~ 40° C)		