



### Features

- LED Backlight
- Support Max. 32CH IP cameras
- H.264 / H.265 Compression Format
- VESA Standard Mount Metal Housing
- ONVIF Protocol Real Time Stream
- Support Max 3840 x 3260 IP Camera

### More Features

Supports up to 3840x2160 IP Cameras

Real-time Streaming Protocol

PTZ Support

Built-In Stand

Sequential

Supports TCP/IP, DHCP, DNS, HTTP, SMTP

H.264 & H.265

	Specification
LCD Panel	32" in ( 812.8 mm )
Visible Area	27.49" x 15.46" in (698.4 x 392.8 mm)
Picture Format	16 : 9
Max Resolution	1920 x1080 ( 1080P )
Pixel Dot Pitch	.014" x .014" in ( 0.36375 x 0.36375mm )
Color	16.7M
Brightness	400 cd/m*2 (LED)
Contrast	4000 : 1
Response Time (Tr / Tf)	8 ms
View Angle (U/D/L/R)	89 / 89 / 89 / 89
Full HD Input	1x HDMI Input
PC Input	1x VGA Input / 1x DVI-D Input
Earphone Out	1 x Phone Jack , 3.5 mm
Speaker	2 x Built-In Speaker ( 2 Watt )
IP Video Support	32 x ( 2592x1944 ) / 25 x ( 2592x1944 ) / 16 x ( 3840x216 ) 8 x ( 3840x2160 ) / 4 x ( 3840x2160 )
Network Port	1 x RJ45, 10M / 100M
USB Port	2 x USB 2.0 Ports
Audio Inputs ( R / L )	2 x RCA
Power input	AC 100-240V 50/60Hz
Power consumption	Approx. 60watt
Dimensions (W x H x D)	29.98" x 17.92" x 3.6" in (761.6 x 455.2 x 93.5mm)
Weight	25.57 lbs. (11.6kgs)
Operating Temperature	32° to 122° F (0° to 50° C)

