



SVN-2564E

64 Channel H.265 DVR



Features

- H.265 & H.264 Video Compression
- 4K Recording All Channels
- Support Add Recorder Feature
- Supports P2P, built in DDNS, DHCP
- Super Live Plus Mobile App

More Features

4K Recording All Channels

Support 8.4MP / 5MP / 4MP / 4MP Lite / 3MP / 1080P / 960P / 720P / Recording

Dual Nic Network Port

OnVif: Profile S

Add Recorder Feature

Utilizes the H.265 High Profile Compression format to ensure high quality video at lower bitrate

NAT and QR Code functionality allows remote access with mobile devices and computers without the need for port-forwarding

Specification	SVN-2564E
Compression	Standard H.265 High Profile
CPU	Cortex A9
OS	Embedded Linux
Input	2 x Dual Nic
Resolution	4K (8.4MP) / 5MP / 4MP, 3MP, 1080P, 720P,
IP Channels	64 Channel
Output	HDMI-1: 4K / 2K / 1920x1080 / 1280x1024, HDMI-2: 1920x1080 / 1280x1024 VGA x 1: 1920x1080 / 128x1024,
Audio port	64 Channel Via IP Camera Support
Two-way Audio	Take Up Channel One Audio Input
Record Resolution	4K (8.4MP) / 5MP / 4MP / 1080P / 720P / WD1
Record Bit Rate	32Kbps~320Mbps
Record Frame Rate	4K (8.4MP) / 5MP / 4MP / 1080P / 720P / WD1 @ 30fps
Mode	Manual / Timer / Motion / Sensor
IP Resolution	Up to 4K (8.4) Megapixel
Storage	8 x Hard Drive (Up to 12 TB each slot)
Play Back	Maximum 16 Channels
Search	Time Slice, Time, Event, Tag Search
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Playback Function	Play / Pause / FF / FB / Digital zoom etc.
Playback Mode	Manual / Sensor / Motion / Exception
Alarm In / Out	16 x Input, 4 x Output
Alarm Trigger	Record / Snap / Preset / E-mail etc.,
Network Interface	RJ45 10 / 100 / 1000 Mbps x 2
Network Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Interface Protocol	Multiple Online User Up to Ten
Smart Phone OS	iOS, Android
PTZ	IP Cameras Support
USB Port	USB 2.0 x 2: 1: Front Panel & 1 Rear Panel
Power Supply	ATX
Power Consumption	<30W (With out Hard Drive)
Operating Temperature	14°F~122°F (-20°C~50°C)
Dimensions	17.5in x 3.5in x 17.7in (445mm x 90 mm x 450mm) (W x H x D)
OnVif	Profile S