



SVD-2404C

4 Channel H.265 DVR



Features

HD-TVI / AHD / HD-CVI / Analog IP
 H.265 / H.264 High Profile Compression
 5, 4, 3 Megapixel / 1080P / 720P / 960H
 BNC, HDMI & VGA Video Output
 2 Additional IP Cameras Support

More Features

HD-TVI / CVI / AHD High Definition Input

Up to 5MP lite/ 4MP / 4MP Lite / 3MP / 1080P / 960P / 720P / WD1 Recording

Two Channels additional IP Camera Support: 2 additional IP cameras.

Convert 4 analog channels to IP (Max 6 IPC)

Utilizes the H.265 High Profile Compression format to ensure high quality video at lower bitrate

NAT and QR Code functionality allows remote access with mobile devices and computers without the need for port-forwarding

| Specification | SVD-2404C |
|-----------------------|--|
| Compression | Standard H.265 High Profile |
| CPU | Cortex A9 |
| OS | Embedded Linux |
| Input | BNC x 4 |
| Resolution | TVI / AHD 5 MP Lite: 4MP Lite, 3MP, 1080P, 720P, WD1 Real Time CVI: 4MP, 3MP, 108P, 720P Real Time |
| IP Channels | 2 Additional, can convert 4 Analog BNC (Max 6 IPC) |
| Output | HDMI x 1: 1920 x 1080, 1280 x 1024, VGA x 1: 1920 x 1080, 128 x 1024, BNC x 1: CVBS (Main or Spot Out) |
| Audio port | 4 x audio inputs, 1 x audio output |
| Two-way Audio | Take Up Channel One Audio Input |
| Record Resolution | 5MP Lite, 4MP lite, 1080P, 1080P Lite, 720P, WD1 |
| Record Bit Rate | 32Kbps-5Mbps |
| Record Frame Rate | 5MP Lite : 10fps (PAL / NTSC): 4MP Lite/ 1080p : 12fps (PAL) / 15fps (NTSC): 1080P Lite / 720P / WD1: 25fps (PAL) / 30fps (NTSC) |
| Mode | Manual, Timer, Motion, Sensor |
| IP Resolution | Up to 5 Megapixel |
| Storage | 1 x Hard Drive (Up to 12 TB) |
| Play Back | Maximum 4 Channels |
| Search | Time Slice, Time, Event, Tag Search |
| Smart Search | Highlighted color to display the camera record in a certain period of time, different colors refers to different record events |
| Playback Function | Play, Pause, FF, FB, Digital zoom etc. |
| Playback Mode | Manual, Sensor, Motion, Exception |
| Alarm In / Out | 4 x Input, 1 x Output |
| Alarm Trigger | Record, Snap, Preset, E-mail, etc., |
| Network Interface | RJ45 10 / 100 Mbps x 1 |
| Network Protocol | TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP |
| Interface Protocol | Multiple Online User Up to Ten |
| Smart Phone OS | iOS, Android |
| PTZ | RS485 x 1 (PTZ or Keyboard) |
| USB Port | USB 2.0 x 2: 1: Front Panel & 1 Rear Panel |
| Power Supply | DC 12V |
| Power Consumption | <12W (With out Hard Drive) |
| Operating Temperature | -4°F~-122°F (-10°C~50°C) |
| Dimensions | 11.6in x 1.65in x 9.65in (295 mm x 42mm x 246mm) (W x H x D) |