



SVN-2516P16C

16 Channel H.265 DVR



Features

- H.265 & H.264 Video Compression
- 16ch 4K Recording All Channel
- Support Add Recorder Feature
- Supports P2P, built in DDNS, DHCP
- Super Live Plus Mobile App

More Features

4K Recording all channels

Add recorder feature

OnVif Profile S H.264 & H.265

Up to 8.4MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P / Recording

Utilizes the H.265 High Profile Compression format to ensure high quality video at lower bitrate

NAT and QR Code functionality allows remote access with mobile devices and computers without the need for port-forwarding

Specification	SVN-2516P16C
Compression	Standard H.265 High Profile
CPU	Cortex A9
OS	Embedded Linux
Input	16 x PoE built In
Resolution	4K (8.4MP) / 5MP / 4MP / 3MP / 1080P / 720P
IP Channels	16 x Channel
Output	HDMI x 1: 4K / 2K / 1920x1080 / 1280x1024 VGA x 1: 1920 x 1080, 128 x1024,
Audio port	16 x audio via IP camera support, 1 x audio output
Two-way Audio	Take Up Channel One Audio Input
Record Resolution	4K (8.4MP) / 5MP / 4MP / 3MP / 1080P / 720P
Record Bit Rate	32Kbps-256Mbps
Record Frame Rate	4K (8.4MP) / 5MP / 4MP / 3MP / 1080P / 720P @30fps
Mode	Manual / Timer / Motion / Sensor / Analytics
IP Resolution	Up to 8.4 Megapixel per Channel
Storage	2 x Hard Drive (Up to 18 TB each slot)
Play Back	Maximum 16 Channels
Search	Time Slice / Time / Event / Tag Search
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Playback Function	Play / Pause / FF / FB / Digital zoom etc.
Playback Mode	Manual, Sensor, Motion, Exception
Alarm In / Out	16 x Input, 4 x Output
Alarm Trigger	Record, Snap, Preset, E-mail, etc.,
Network Interface	RJ45 10 / 100 Mbps x 1
Network Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Interface Protocol	Multiple Online User Up to Ten
Smart Phone OS	iOS, Android
PTZ	RS485 x 1 (PTZ or Keyboard)
USB Port	USB 2.0 x 2: 1: Front Panel & 1 Rear Panel
Power Supply	ATX
Power Consumption	<30W (With out Hard Drive)
Operating Temperature	14°F~122°F (-20°C~50°C)
Dimensions	17.3in x 3.5in x 177in (440 mm x 89 mm x 450 mm) (W x H x D)
Remote Control	Included