



CC04-IP3MV

Industrial IP Networking Camera



Features

Triple Stream H.265 & H.264 & M-JPEG
 Max. 3 Megapixel (2048x1536) @ 30fps
 Rugged Vibration Damping Mount
 RJ45 Connecion (M12 Optional)
 Supports OnVif (Profile S) Standard
 IP-67 Weatherproof / Dustproof

More Features

5 Megapixel Max (2592x1944)

Sony Stavis 1 / 2.8" With
 5.14MP Image Sensor

Native Support for Deep
 Learning AI Feature

Quadruple Streaming (h.265,
 h.264, M-Jpeg, Jpeg)

Max 30fps @ 5Megapixel

Various back light mode of
 WDR, BLC, HLC,

D-WRD, D-Zoom, Defog

OnVif Profile S, T

Multi Browser Support
 (Chrome & Edge)

Specification	CC04-IP3MV
Imaging Sensor	½.8" 3.21MP Sony Starvis PS CMOS
Lens	2.85mm (F1.6) / 6.0mm (F2.0) Fixed Lens
Day & Night	True Day & Night (ICR)
Min. Illumination	Color : 0.05 lux / B/W : 0.0005 lux (IIR ON)
System	64bit RISC-V Quad Core up to 594MHz, NAND Flash 2Gb / LPDDR3 4Gb
Compression	H.265, H.264, M-JPEG, JPEG
Resolution	2048x1536 / 1920x1080 / 1280x720 704x480 / 640x352 / 320x176 / 160x96
Frame Rate	Max 3 Megapixels (2048x1536) @30 fps / 2 Megapixel @ 60fps
Motion Detection	4 Areas
Privacy Masking	8 Areas
Smart Video	ROI
Video Stream	Quad Streaming, selectable : H.265 / H.264 / MJPEG, JPEG Frame rate, Bit rate, VBR / AVBR / CBR / ACBR / GOP
Exposure Mode	Indoor / Outdoor
AE Metering Mode	Spot / Center / Average / Venter Flip
Shutter Control	Manual (Min. /Max. Setting) Auto
Max AGC Gain	0 – 72
Sense Up Level	Off / 1 / 2
Back Light Compensation	Enable / Disable
Auto Exposure	25% - 400%
Playback Mode	DOL WDR (Enable / Disable) D-WDR 0-128
Image Adjustment	Brightness / Contrast / Hue / Saturation / Sharpness
White Balance	Auto / Manual / Preset
Connection	RJ45 PoE, 2.1mm Optional power (M12 Connection Optional)
Day & Night Control	Color / Black & White / Auto Night / Color (B/W, 10 ,20, 30, 40, 50)
Image Direction	Vertical Flip / Horizontal Flip / Corridor Mode
Programing Interface	SDK, ONVIF Profile S, T
Illuminator	8 IR LED's Max. Distance 32.8 ft (10 Meter)
Power Supply	SMPS, DC12V 1Amp & PoE IEEE 802.3af
Power Consumption	Max. 4.0W
Operating Temp.	-20C ~ + 60C, (-4F ~ 140F) 10% ~ 90% RH
Dimension	80 (W) X 70 (L) X 54 (H) mm
Weight	About 370g without Braket
Approval	KC, CE, FCC, RoHS, IP67