



CC04-IP3MV

Industrial IP Networking Camera



Features

Triple Stream H.265 & H.264 & M-JPEG
 Max. 3 Megapixel (2048x1536) @ 30fps
 Rugged Vibration Damping Mount
 Night Color With Super High Sensitive Sensor
 Supports OnVif (Profile S) Standard
 IP67 Weatherproof / Dustproof

More Features

3 Megapixel h.265&h.264

Support Protocol: HTTP, RTP/RTSP (Uni/Multicast), TCP/IP (v4/v6), UDP, FTP, Telnet, HTTPS, RARP, SNMP, DHCP, NTP, SMTP client, UPNP & etc.

Security, IP filtering, HTTPS, Encrypted & Basic Authentication, Management White List

Video Out RJ45 & 1CVBS

Metal Cases IP 67 rated

Shutter Limit (min./max setting)

Specification	CC04-IP3MV
Imaging Sensor	1/2.8" 3.21MP Sony Starvis PS CMOS
Lens	2.85mm (F1.6) / 6.0mm (F2.0) Fixed Lens
Day & Night	True Day & Night (ICR)
Min. Illumination	Color : 0.05 lux / B/W : 0.0005 lux (IIR ON)
System	Ambarella 32bit Embedded Linux, 256Mbyte SDRAM, 12Mbyte NAND Flash
Compression	H.265, H.264, M-JPEG,
Resolution	2048x1536 / 1920x1080 / 1280x720 704x480 / 640x352 / 320x176 / 160x96
Frame Rate	Max 3 Megapixels (2048 x 1536) @30 fps
Motion Detection	4 Areas
Privacy Masking	8 Areas
Smart Video	ROI
Video Stream	Triple Streaming, selectable : H.265 / H.264 / MJPEG, Frame rate, Bit rate, VBR / AVBR / CBR / ACBR / GOP
Exposure Mode	Indoor / Outdoor
AE Metering Mode	Spot / Center / Average / Venter Flip
Shutter Control	Manual (Min. /Max. Setting) Auto
Max AGC Gain	0 - 72
Sense Up Level	Off / 1 / 2
Back Light Compensation	Enable / Disable
Auto Exposure	25% - 400%
Playback Mode	DOL WDR (Enable / Disable) D-WDR 0-128
Image Adjustment	Brightness / Contrast / Hue / Saturation / Sharpness
White Balance	Auto / Manual / 9 Special Condition
3DNR	0 -11
Day & Night Control	Color / Black & White / Auto Night / Color (B/W, 10 ,20, 30, 40, 50)
Image Direction	Vertical Flip / Horizontal Flip / Corridor Mode
Programing Interface	SDK, ONVIF Profile S
Illuminator	8 IR LED's Max. Distance 32.8 ft (10 Meter)
Power Supply	SMPS, DC12V 1Amp & PoE IEEE 802.3af
Power Consumption	Max. 5.2W
Operating Temp.	-10C ~ + 50C, 10% ~ 90% RH
Dimension	80 (W) X 50 (D) X 54 (H) mm
Weight	About 515g without Power supply
Approval	KC, CE, FCC, RoHS, IP67