



MIP-4125

4MP 25X IP PTZ Camera



Features

- 1/ 2.5" 4MP Resolution
- Smart IR with 330ft distance
- Powerful 25x Optical Zoom
- IP66 Rated
- Max 25/30fps @ 4MP
- POE+ / SD slot

More Features

High Efficiency Video Coding

WDR, HLC, BLC, 3DDNR, Defog

360° Endless

Smart Event: Motion Detection, Intrusion, Object abandoned/missing

Alarm Linkage: Alarm Action, such as preset, cruise track SD card recording, trigger recording, notify surveillance center, upload to ftp/sd card/NAS send E-mail, ect.

Smart Record: ANR (Automatic Network Replenishment)

IP 66 Rated

Specification	MIP-4125
Image Sensor	1/2.2" Progressive Scan CMOS
Min. Illumination	Color: 0.01 lux; B/W: 0 lux with IR on
S/N Ratio	More than 50dB
Effective Pixels	4 Megapixel (IP)
Lens	25 x Optical Zoom, F=4.8-120mm, F1.6 ~ F3.5
Video Compression	H.265 / H.264 / MJPEG
Resolution	4 Megapixel, 3 Megapixel, 1080P, 720P
Multi-Stream	Main: 50Hz: 25fps / 60Hz: 30 fps (2560X1440, 1920x1080, 1280x720) Sub: 50Hz: 25fps (1280x720, D1, CIF) / 60Hz: 30fps (D1, 480x240, CIF) Third: 50Hz: 25fps / 60Hz: 30fps (D1, 480x240, CIF)
Protocol	HTTP, HTTPS, IPv4/IPv6, 802.1x, QoS, UPnP, SNMP, DNS, RTCP, RTP, IGMP, ICMP, TCP/IP, UDP, DHCP, DDNS, NTP, RTSP, SMTP, FTP, PPPoE
Storage	Built-In Micro SD Card Slot, Network Remote storage
Pan	Range: 360° Endless; Speed: 0.5°/s to 80°/s; Preset Speed: 80°/s
Tilt	Range: -5° to 90° (Auto-flip); Speed: 0.5°/s to 80°/s; Preset Speed: 80°/s
Cruise	8 Cruises, 16 Presets for each cruise
Smart Alarm	Motion Alarm, Sensor Alarm
Preset	255
PTZ Mode	Cruise: 8, Track: 4, Scan: 2
Scan	2 Scans
Track	4 Tracks, 3 Minutes of recording for each track
IR LEDs	330ft (100m)
IR Control	Supports Smart IR
Weatherproof Rating	IP66
Network Interface	RJ45 x 1, 10M / 100M Self Adaption
Max. User Access	16 Users, 3 Levels: Admin, Advanced, Normal
API	API, SDK, ONVIF, GB / T28181
RS485	RS485 x 1
Smartphone	iPhone, iPad, Android, Windows Phone
Web Browser	IE8 - 11, Chrome 31.0 - 44, Firefox 30.0 - 51
Power Supply	DC 12v 3Amp, PoE +, PC+10%GF 23W
Operating Temperature	-22° ~ 131°F (-30° ~ 55°C) 10% ~90% Relative Humidity
Weight	8.3lb, 3.7kg