

SVN-2504P4C 4 Channel H.265 DVR



Features

H.265 & H.264 Video Compression 4K Recording All Channels Support Add Recorder Feature Supports P2P, built in DDNS, DHCP Super Live Plus Mobile App

More Features

4K Recording All Channels

Up to 8MP / 5MP / 4MP / 4MP Lite / 3MP / 1080P / 960P / 720P / WD1 Recording

Support OnVif Profile S Third Party

Utilizes the H.265 High Profile Compression format to ensure high quality video at lower bitrate

NAT and QR Code functionality allows remote access with mobile devices and computers without the need for port-forwarding

| Specification | SVN-2504P4C |
|-----------------------|--|
| Compression | Standard H.265 High Profile & H.264 |
| CPU | Cortex A9 |
| OS | Embedded Linux |
| Input | 4 x PoE Built in |
| Resolution | 8MP /5MP/ 4MP / 3MP / 2MP / 1080P / 720P |
| IP Channels | 4 |
| Output | HDMI x 1: 4K (3840x2160), 1920x1080, 1280x1024, VGA x 1: 1920x1080, 128x1024, |
| Audio port | 1 x audio inputs, 1 x audio output |
| Two-way Audio | Take Up Channel One Audio Input |
| Record Resolution | 8MP /5MP / 4MP / 3MP / 2MP / 1080P / 720P |
| Record Bit Rate | 32Kbps~4Mbps |
| Record Frame Rate | 8MP /5MP/ 4MP / 3MP / 2MP / 1080P / 720P @30fps |
| Mode | Manual, Timer, Motion, Sensor, Analytics |
| IP Resolution | Up to 8 Megapixel |
| Storage | 1 x Hard Drive (Up to 18 TB) |
| Play Back | Maximum 4 Channels |
| Search | Time Slice, Time, Event, Tag Search |
| Smart Search | Highlighted color to display the camera record in a certain period of time, different colors refers to different record events |
| Playback Function | Play, Pause, FF, FB, Digital zoom etc. |
| Playback Mode | Manual, Sensor, Motion, Exception |
| Alarm In / Out | 4 x Input, 1 x Output |
| Alarm Trigger | Record, Snap, Preset, E-mail, etc., |
| Network Interface | RJ45 10 / 100 Mbps x 1 |
| Network Protocol | TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP |
| Interface Protocol | Multiple Online User Up to Ten |
| Smart Phone OS | iOS, Android |
| PTZ | IP Interface only |
| USB Port | USB 2.0 x 2: 1: Front Panel & 1 Rear Panel |
| Power Supply | DC 48V |
| Power Consumption | <5W (With out Hard Drive) |
| Operating Temperature | -4°F~122°F (-20°C~50°C) |
| Dimensions | 11.6in x 1.6in x 9.6in (295 mm x 42mm x 246mm) (W x H x D) |
| Remote Control | Yes |

Office:

800-578-1853