



MIB-8131SV4

4K/8MP H.265 IR Bullet IP Camera



Features

H.265+. H.265, H.264, MJPEG, Video Compression
 IR LEDs (Up to 100ft.) 3D DNR, S-WDR (True)
 Built-in SD Slot (256GB max.)
 Two Way Audio Support
 IP67 Ingress / Protection
 Supports Triple Streaming

More Features

H.265+/H.265, H.264+/H.264,
 MJPEG Coding

Max. Resolution 8 Megapixel
 (3840 x 2160)

ICR auto switch, True Day/Night
 vision

3D DNR, True WDR, HLC, BLC,
 Smart IR and Roi Coding

100ft IR Night Vision

Built-in SD Slot (256GB max.)

DC 12v / PoE Power

IP 67 Weatherproof rated

Intelligent Analytics Support

1ch Audio Input

Fixed 2.8mm Wide lens

Smart Alarm Trigger

Certification CE, FCC

Specification	MIB-8131SV4
Sensor	1/2.8" Progressive Scan CMOS
Electronic Shutter	1/20,000s~1/5s
Auto Iris	Fixed Iris
Min. Illumination	0.01 Lux @ F1.2, AGC ON; 0 Lux with IR
Lens	2.8mm Fixed Lens (ICR)
Lens Mount	Fixed
Day & Night	ICR
Angle Adjustment	Any Angle
Video Compression	H.265 MP; H.264 BP / MP / HP; MJPEG
Resolution	8.4MP (3840x2160) 1080P (1920x1080) 720P (1280x720) D1 CIF 480x240
Main-Stream	60Hz: 8MP / 1080P / 720P (1~30fps) 50Hz: 8MP / 1080P / 720P (1~25fps)
Bit Rate	64Kbps~16Mbps
Encode Mode	VBR/CBR
Quality	Five Levels Under VBR, Freely Adjustable under CBR
Image Setting	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. Adjustable Through Client Software or Web Browser
Audio Compression	G711A/U (Input port)
ROI	Each ROI to be Configured Separately
Network	RJ45 x 1, 10M/100M Self-Adaptation
Audio	MIC IN x 1, MIC OUT x 1
Video Output	CVBS Video Output (BNC x1)
Remote Monitoring	IE Browsing, CMS Remote Control
Online Connections	Simultaneous Stream up to ten users / Multi-Stream Real Time Transmission
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
Interface Protocol	ONVIF, GB-T/28181-2011
Storage	Network Remote Storage
Smart Alarm	Motion Alarm
PoE	Yes
Weatherproof Rating	IP67
Power Supply	DC12V/PoE (802.3af), 7W
Power Consumption	<7W (IR ON <9W)
Operating Temperature	-22°F ~ 140°F (-30°C ~ 60°C)
Dimensions	6.5in x 2.9in (167.5mm x 74.5mm)
Weight	.97 lbs (44KG)