



MIP-4103

4 Megapixel 3x Mini PTZ




Features

- 4 Megapixel Mini PTZ
- Powerful 3x Optical Zoom
- 120dB True WDR
- IP67, IK10 Protection
- Support PoE / 12V DC

More Features

- Starlight Megapixel PTZ
- Powerful 3x Optical Zoom
- True WDR 120dB
- 12V DC & PoE
- IP67 IK10 Protection
- Micro SD slot
- OnVif Protocol Compatible G, S, T
- Triple Stream



Specification	MIP-4103
Image Sensor	1/ 2.7" progressive scan CMOS with BSI and NIR+ technology
Image Resolution	(H) 2688 x 1520 (V) (4.08MP)
Audio	Built In Mic /
Alarm	1ch alarm input (dry connection); 1ch alarm output
Electric Shutter	1/30 s- 1/30,000 s
Minimum Illumination	0.02 Lux @ F1.6 (color) & 0.04 Lux @ F1.6 (B?W)
S/N Ratio	> 52dB
Lens Type	Motorized
Focal Length	3.8 – 7.42mm
Angle of View	Horizontal 113.6 – w / -44.3 W degrees
Max Aperture	F1.6 – F2.7
Pan / Tilt Range	Pan 0-355 degree/ Tilt 15-90 degree /auto flip 180 degree
Preset Speed	0.5 – 80/s
Preset	360
PTZ Mode	5 Pattern, 8 Tour, Auto Pan, 5 Auto Scan
Speed Setup	Human-oriented focal length / Speed adaptation
Power UP Action	Auto restore to previous PTZ & lens status after power failure
Idle Motion	Active Preset/Scan/Tour / Pattern if there is no command in the Special period
Protocol	HTTP, HTTPS, IPV4/IPV6, 802.1x, FTP, SMTP, UPNP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, P2P
Video Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Streaming Capability	10 Streams
Resolution	2688x1520, 2560x1440, 2048x1536, 1920x1080, 1280x720, 704x576 / 704x480
Bit Rate Control	CBR / VBR
Video Bitrate	H.264 / H.265: 128 Kbps – 12,288 Kbps
Day / Night	Auto (ICR) ; Color B/W
BLC Mode	Support
Network Interoperability	Compatible OnVif G & S & T, PSIA, CGI
Storage	Micro SD Card Slot (Support Max 256GB)
Power Supply	12V DC / 2.0A, Poe (802.3af)
Power Consumption	<12 W
Operation Temp.	-30-60 C / -22 – 140 F < 95% RH
Protection	IP67, IK10
Casing	Metal
Dimensions	116 x 75mm / 4.56 x 2.95 in
Weight	463g / 1.0 lbs