

IPS-3000

Mini Video Server



Features

- H.265 & H.264 Video Compression
- Support Opticom, Onvif, RTSP, SDK Protocol
- Support User Account
- Dual USB for Mouse & Keyboard
- Digital Zoom support



Specification	IPS-3000
CPU	Intel® Pentium 4405U
Memory	DDR4, 8GB
Graphis Card	Integrated Graphics, Intel® HD Graphics 510
Operation System	Linux
Software	Opticom NVMS standard (custom)
Decoding Capability	6CH 8MP or 8CH 5MP or 10CH 4MP or 16CH 1080P or 23CH 720P or 30CH D1 (or lower)
Max. Channel Access	256CH
Max. Device Access	64 devices
Max. User Access	Max. 64 users
Max. Decoding Output	32
Max. of Transfer Server Access	1
Max. Channel Access Third-party protocol	256 ch
Max. Device Access Third-party protocol	64
Max. Channel Simultaneous Preview	64 (for one client/user)
Max. Views	Up to 64 view plans can be created
Max. Outgoing bandwidth	100Mbps
Max. Online Users	5 users preview simultaneously
Protocol	Private Opticom protocol, SDK, ONVIF, RTSP,
PTZ Control	zoom in, zoom out, preset, cruise, 3D control
System HDD	mSATA SSD 128GB
Video Output	1CH HDMI @ 4K / 1 VGA @ 1080P
Ethernet Interface	1 RJ45 10M/100M/1000M self-adaptive Ethernet port
Power	DC 12V/3A
Power Consumption	≤36W
Working Temp.	-5°C--+45°C / 23F+113F
Storing Temp.	-20°C--+70°C / -4F--+158F
Working Humidity	10%--95%
Dimensions	WxHxD 154x120x30 mm / 6.06x4.72x1.18
Weight	≤0.47Kg / ≤1.03Lbs